

HEAT-SHRINK CRIMP BUTT CONNECTOR



Illustration only

Art. No.	0555 510 0	0555 510 1	0555 510 2	0555 510 4
P. Qty.	50 / 100	50 / 100 / 300	50 / 100 / 300	50 / 100
Min./max. wire cross section	0.2-0.5 mm ²	0.5-1.5 mm ²	1.5-2.5 mm ²	4-6 mm ²
Colour	Transparent	Red	Blue	Yellow
Dielectric strength	30 kV/mm	30 kV/mm	30 kV/mm	30 kV/mm
IP protection class	IP 67	IP 67	IP 67	IP 67
Min./max. temperature conditions	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C
Min. shrinkage temperature	300 °C	300 °C	300 °C	300 °C
Length	30 mm	35 mm	35 mm	40 mm

Can be stored in ORSY

Application area

Dust-proof and damp-proof connections. Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.

Notice

Avoid localised overheating of the heat-shrink tubing.

Semi-transparent heat-shrink tubing

Straightforward visual monitoring of the connection

40% quicker shrinking behaviour

Time-saving

Low shrinking temperature of +100°C

Low risk of damage for connector and cable insulation

Proof of Performance

RoHS-compliant

HEAT-SHRINK CRIMP CONNECTOR SPADE TERMINAL



Illustration only

Art. No.	0555 513 104	0555 513 204	0555 513 205	0555 513 404	0555 513 405
P. Qty.	50 / 100	50 / 100	50	50	50
Min./max. wire cross section	0.5-1.5 mm ²	1.5-2.5 mm ²	1.5-2.5 mm ²	4-6 mm ²	4-6 mm ²
Colour	Red	Blue	Blue	Yellow	Yellow
Flange hole	M4	M4	M5	M4	M5
Dielectric strength	30 kV/mm	30 kV/mm	30 kV/mm	30 kV/mm	30 kV/mm
IP protection class	IP 67	IP 67	IP 67	IP 67	IP 67
Min./max. temperature conditions	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C	-55 to 125 °C
Min. shrinkage temperature	300 °C	300 °C	300 °C	300 °C	300 °C

Can be stored in ORSY

Application area

Dust-proof and damp-proof connections. Good to excellent resistance against petrol, battery acid, diesel, engine oil, anti-freeze, brake fluid, 5% saline solution, isopropyl alcohol.

Notice

Avoid localised overheating of the heat-shrink tubing.

Semi-transparent heat-shrink tubing

Straightforward visual monitoring of the connection

40% quicker shrinking behaviour

Time-saving

Low shrinking temperature of +100°C

Low risk of damage for connector and cable insulation

Proof of Performance

RoHS-compliant