

SET SCREWS

DIN EN ISO 4026

replaces DIN 913

with Allen socket and truncated cone

A2 stainless steel, 21 H

A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of 210 HV.

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M5	14	0261 5 14	200		
	16	0261 5 16		0221 5 16	200
	20	0261 5 20		0221 5 20	
	25	0261 5 25	100	0221 5 25	
	30	0261 5 30		0221 5 30	100
	35	0261 5 35		0221 5 35	
	40	0261 5 40		0221 5 40	
	45	0261 5 45			
	50	0261 5 50			
M6	4	0261 6 4	100		
	5	0261 6 5		0221 6 5	100
	6	0261 6 6		0221 6 6	
	8	0261 6 8		0221 6 8	
	10	0261 6 10		0221 6 10	
	12	0261 6 12		0221 6 12	
	16	0261 6 16		0221 6 16	
	18	0261 6 18			
	20	0261 6 20		0221 6 20	
	25	0261 6 25		0221 6 25	
	30	0261 6 30		0221 6 30	
	35	0261 6 35		0221 6 35	
	40	0261 6 40		0221 6 40	
	45	0261 6 45			
	50	0261 6 50		0221 6 50	
	55	0261 6 55			
	60	0261 6 60		0221 6 60	200
	70	0261 6 70			
	80	0261 6 80			
M8	6	0261 8 6	100		
	8	0261 8 8		0221 8 8	100
	10	0261 8 10		0221 8 10	
	12	0261 8 12		0221 8 12	
	14	0261 8 14		0221 8 14	200
	16	0261 8 16		0221 8 16	100
	18	0261 8 18		0221 8 18	200
	20	0261 8 20		0221 8 20	100
	25	0261 8 25		0221 8 25	
	30	0261 8 30		0221 8 30	
	35	0261 8 35		0221 8 35	
	40	0261 8 40		0221 8 40	
	45	0261 8 45		0221 8 45	
	50	0261 8 50		0221 8 50	
	55	0261 8 55			
	60	0261 8 60		0221 8 60	
	70	0261 8 70			
	80	0261 8 80			
	100			0221 8 100	100
M10	10	0261 10 10	100	0221 10 10	100
	12	0261 10 12		0221 10 12	
	16	0261 10 16		0221 10 16	

Can be stored in ORSY®

DIN 913 has been retracted and replaced by international standard DIN EN ISO 4026.