



# Hexagon Bolts with fine thread DIN 960

**Steel 10.9  
Zinc-nickel  
Transparent passivated (P3E)**

- **Chrome (VI)-free:**  
→ Fulfills the EU End-of-Life Vehicles Directive.
- **Corrosion resistance:**  
→ 720 h base metal corrosion pursuant to DIN EN ISO 9227-NSS (DIN 50021-SS) – in comparison: 96 h yellow galvanised (A2C).

Thread dia. d	M 8x1	M 10x1	M 12x1.5	M 14x1.5	M 16x1.5	M 18x1.5	M 20x1.5	M 24x1.5
b (up to 125) in mm	22	26	30	34	38	42	46	54
b (125 to 200) in mm	28	32	36	40	44	48	52	60
k in mm	5.3	6.4	7.5	8.8	10	11.5	12.5	15
s in mm	13	17	19	22	24	27	30	36

Thr. dia. d	Thread pitch	l in mm	Special thread length b similar DIN 960 in mm	Art. No.	P. Qty.
M 8	1.0	25	18	<b>0263 48 25</b>	100
		30	18	<b>0263 48 30</b>	
		40	18	<b>0263 48 40</b>	
M 10	1.0	30	20	<b>0263 410 30</b>	50
		35	22	<b>0263 410 35</b>	
		40		<b>0263 410 40</b>	
		45		<b>0263 410 45</b>	
		50		<b>0263 410 50</b>	
		60		<b>0263 410 60</b>	
M 12	1.5	70		<b>0263 410 70</b>	50
		30	20	<b>0263 412 30</b>	
		35	22	<b>0263 412 35</b>	
		40	22	<b>0263 412 40</b>	
		45	22	<b>0263 412 45</b>	
		50	22	<b>0263 412 50</b>	
		55		<b>0263 412 55</b>	
		60	32	<b>0263 412 60</b>	
		70		<b>0263 412 70</b>	
		80		<b>0263 412 80</b>	
M 14	1.5	90		<b>0263 412 90</b>	25
		100		<b>0263 412 100</b>	
		120		<b>0263 412 120</b>	
		35	24	<b>0263 414 35</b>	
		40	24	<b>0263 414 40</b>	
		45	24	<b>0263 414 45</b>	
		50	24	<b>0263 414 50</b>	
		55	24	<b>0263 414 55</b>	
		60	24	<b>0263 414 60</b>	
		65		<b>0263 414 65</b>	
		70	24	<b>0263 414 70</b>	
		80	24	<b>0263 414 80</b>	
90		<b>0263 414 90</b>			
100		<b>0263 414 100</b>			
110		<b>0263 414 110</b>			
120		<b>0263 414 120</b>			
140		<b>0263 414 140</b>			
160		<b>0263 414 160</b>			

Thr. dia. d	Thread pitch	l in mm	Special thread length b similar DIN 960 in mm	Art. No.	P. Qty.
M 16	1.5	35	28	<b>0263 416 35</b>	50
		40	28	<b>0263 416 40</b>	
		45	28	<b>0263 416 45</b>	
		50	28	<b>0263 416 50</b>	
		55	28	<b>0263 416 55</b>	
		60	28	<b>0263 416 60</b>	
		65		<b>0263 416 65</b>	
		70		<b>0263 416 70</b>	
		75		<b>0263 416 75</b>	
		80		<b>0263 416 80</b>	
		90		<b>0263 416 90</b>	
		100		<b>0263 416 100</b>	
120		<b>0263 416 120</b>			
130		<b>0263 416 130</b>			
140		<b>0263 416 140</b>			
150		<b>0263 416 150</b>			
160		<b>0263 416 160</b>			
180		<b>0263 416 180</b>			
M 18	1.5	50	26	<b>0263 418 50</b>	50
		60		<b>0263 418 60</b>	
		70		<b>0263 418 70</b>	
		80		<b>0263 418 80</b>	
		100		<b>0263 418 100</b>	
M 20	1.5	120		<b>0263 418 120</b>	25
		140		<b>0263 418 140</b>	
		60		<b>0263 420 60</b>	
		70		<b>0263 420 70</b>	
		80		<b>0263 420 80</b>	
		90		<b>0263 420 90</b>	
		100		<b>0263 420 100</b>	
		120		<b>0263 420 120</b>	
M 24	1.5	140		<b>0263 420 140</b>	25
		160		<b>0263 420 160</b>	
		80		<b>0263 424 80</b>	
		90		<b>0263 424 90</b>	
		100		<b>0263 424 100</b>	
		120		<b>0263 424 120</b>	

