






# RW 1400 AGITATOR

Suitable agitating baskets							
Application	Appearance	Description	Length in mm	Basket diameter in mm	Mixed material in kg	Shank mounting	Art. No.
R I For liquid materials		Wall paints, dispersion paints, lacquers, primers and lots more  Mixing effect: from the top down	400	80	5-10	Width 8	<b>0713 95 100</b>
			590	100	10-25	Width 10	<b>0713 95 101</b>
			590	120	20-30	Width 10	<b>0713 95 103</b>
R II For tough and sticky materials		Ready-mixed plaster, mortar, gypsum, tile cement, fillers, cement slurries and lots more  Mixing effect: from the bottom up	400	90	5-10	Width 8	<b>0713 95 110</b>
			590	120	15-25	M14	<b>0713 95 111</b>
			590	120	15-25	Width 10	<b>0713 95 112</b>
			590	140	25-35	M14	<b>0713 95 113</b>
M I For heavy materials		Plaster, mortar, concrete, cement, screed and lots more  Mixing effect: from the bottom up	590	120	15-25	M14	<b>0713 95 120</b>
			590	140	25-40	M14	<b>0713 95 121</b>
			590	160	40-60	M14	<b>0713 95 122</b>
M II For powdery and sticky materials		Ready-mixed mortars, tile cements, joint mortars, flooring adhesives, adhesive mortars, pastes and lots more  Mixing effect: from the bottom up	400	85	5-10	Width 8	<b>0713 95 130</b>
			590	105	10-15	M14	<b>0713 95 131</b>
			590	105	10-15	Width 10	<b>0713 95 132</b>
- Agitator with high shear force for blending viscous materials		Fillers, adhesive mortars, thick coatings, adhesive compounds, sealing compounds and lots more  Mixing effect: swirling	590	140	25-35	M14	<b>0713 95 137</b>

\*For agitating baskets with 8/10 mm shank mounting, we recommend using the Würth BS 13-SEC POWER Driver Drill (Art. No. 0702 315 1).