

INSULATED CLOSABLE CORRUGATED PIPE, SLIT



Preassembled cable harnesses can be retrofitted in a quick and simple process.

Precise overlap of the pipe slitting

- In contrast to the basic slit insulated corrugated pipe.
- No gaps at bends
Wires and conductors remain clean and protected

Resistant to alcohols, greases, mineral oils, diesel fuels and petrol

Art. No.	0771 980 004	0771 980 007	0771 980 010	0771 980 013	0771 980 017	0771 980 019
P. Qty.	100	50	50	50	50	50
Colour	Black	Black	Black	Black	Black	Black
Nominal width	4.5 mm	7.5 mm	10 mm	13 mm	17 mm	19 mm
Outer diameter	7.1 mm	10.1 mm	13.0 mm	15.8 mm	21.0 mm	24.0 mm
Internal diameter	4.7 mm	6.6 mm	9.8 mm	12.9 mm	16.8 mm	19.0 mm
Flammability	Self-extinguishing in accordance with UL94 V2	Self-extinguishing in accordance with UL94 V2	Self-extinguishing in accordance with UL94 V2	Self-extinguishing in accordance with UL94 V2	Self-extinguishing in accordance with UL94 V2	Self-extinguishing in accordance with UL94 V2
Min./max. temperature conditions	-40 to 105 °C	-40 to 105 °C	-40 to 105 °C	-40 to 105 °C	-40 to 105 °C	-40 to 105 °C
Material	PP - Polypropylene	PP - Polypropylene	PP - Polypropylene	PP - Polypropylene	PP - Polypropylene	PP - Polypropylene
Halogen-free	Yes	Yes	Yes	Yes	Yes	Yes
Ultraviolet resistance	Yes	Yes	Yes	Yes	Yes	Yes

Scope of delivery: Includes fitting tool

Application area

E.g. engine compartment, bodywork, vehicle interior, machine/apparatus construction, switch cabinets, protecting vehicle wiring against heat, moisture, chemicals and UV irradiation.