

## CURRENT TRANSFORMER WÜRTH FLEX 400



**Digital TRMS ammeter with flexible measurement loop allows measurement at inaccessible conductors. The ideal addition for every electrician.**

### Current measurement:

AC, starting from just a few mA

**Flexible current measurement loop with shielded cable securely attached to housing**

### Innovative closing system of the measurement loop

For extremely easy handling at hard-to-reach points

### MAX HOLD function for the maximum value — memory

e.g. to monitor a plant in idle/continuous operation

- Large LCD display for optimum readability
- 4000 count resolution for high levels of accuracy
- Automatic range selection and power off

|                                            |                   |
|--------------------------------------------|-------------------|
| Art. No.                                   | 0715 58 660       |
| P. Qty.                                    | 1                 |
| Display                                    | 4000 digits       |
| Enclosure diameter                         | 45 mm             |
| Min./max. current measuring range          | 20 mA/AC-400 A/AC |
| Overvoltage protection category            | CAT IV/600 V      |
| IP protection class                        | IP 40             |
| Rechargeable battery/battery designation   | 1.5 V Micro AAA   |
| Number of rechargeable batteries/batteries | 2 PCS             |

|                    |          |
|--------------------|----------|
| Related products   | Art. No. |
| Battery High Power | 0827 111 |

### Application area

For applications in the low-voltage range at small and medium powers, such as maintenance of electrical installations in service or industry.

### Notice

Refer to the technical data sheet for a detailed description of the innovative functions and measured values.