

## ATO FLAT PLUG-IN FUSE SILVER



Silver-plated version for improved heat removal

OEM quality

Max. amperage	Color	Max. nominal voltage	Min./max. operating temperature	Surface of contacts	Art. No.	P. Qty.
1 A	Black	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 01</b>	25
2 A	Gray	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 02</b>	25
3 A	Purple	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 03</b>	25
4 A	Pink	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 04</b>	25
5 A	Brown	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 05</b>	25
7.5 A	Ocher brown	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 075</b>	25
10 A	Red	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 10</b>	25
15 A	Turquoise	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 15</b>	25
20 A	Yellow	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 20</b>	25
25 A	White	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 25</b>	25
30 A	Green	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 30</b>	25
35 A	Blue	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 35</b>	25
40 A	Orange	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 314 40</b>	25

Suitable for ORSY storage

## FLAT PUSH-IN FUSE SILVER



Silver-plated version for improved heat removal

OEM quality

Max. amperage	Color	Max. nominal voltage	Min./max. operating temperature	Surface of contacts	Art. No.	P. Qty.
20 A	Yellow	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 20</b>	10
30 A	Green	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 30</b>	10
40 A	Orange	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 40</b>	10
50 A	Red	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 50</b>	10
60 A	Blue	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 60</b>	10
70 A	Brown	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 70</b>	10
80 A	White	32 V/DC	-40 to 125 °C	Silver-plated	<b>0731 301 80</b>	10

Suitable for ORSY storage