



# Wire End Ferrules

with Plastic Sleeves  
DIN 46228 Part 4

- Sleeve: Cu, galvanized.
- Halogene free.

Cross section mm <sup>2</sup>	Colour acc. to DIN 47002	l <sub>1</sub>	l <sub>2</sub>	d <sub>1</sub>	s <sub>1</sub>	d <sub>2</sub>	s <sub>2</sub>	Art. No.	Pack Qty.
0.5	white	12.0	6.0	1.0	0.15	2.6	0.25	<b>0557 300 051</b>	500, 1000
		14.0	8.0					<b>0557 300 052*</b>	100, 500, 1000
		16.0	10.0					<b>0557 300 053</b>	500
0.75	grey	12.0	6.0	1.2	0.15	2.8	0.25	<b>0557 300 751</b>	500, 1000
		14.0	8.0					<b>0557 300 752*</b>	100, 500, 1000
		16.0	10.0					<b>0557 300 753</b>	500, 1000
		18.0	12.0					<b>0557 300 754</b>	100
1.0	red	12.0	6.0	1.4	0.15	3.0	0.25	<b>0557 300 101</b>	500, 1000
		14.0	8.0					<b>0557 300 102*</b>	100, 500, 1000
		16.0	10.0					<b>0557 300 103</b>	500, 1000
		18.0	12.0					<b>0557 300 104</b>	500
1.5	black	14.0	8.0	1.7	0.15	3.5	0.25	<b>0557 300 151*</b>	100, 500, 1000
		16.0	10.0					<b>0557 300 152</b>	500, 1000
		24.0	18.0					<b>0557 300 153</b>	500
2.5	blue	14.0	8.0	2.2	0.15	4.2	0.25	<b>0557 300 251*</b>	100, 500, 1000
		18.0	12.0					<b>0557 300 252</b>	500, 1000
		24.0	18.0					<b>0557 300 253</b>	500
4.0	grey	17.0	10.0	2.8	0.20	4.8	0.30	<b>0557 300 401*</b>	100, 1000
		20.0	12.0					<b>0557 300 402</b>	100, 1000
		26.0	18.0					<b>0557 300 403</b>	100
6.0	yellow	20.0	12.0	3.5	0.20	6.3	0.30	<b>0557 300 601*</b>	100, 500
		26.0	18.0					<b>0557 300 602</b>	100, 500
10.0	red	22.0	12.0	4.5	0.20	7.6	0.40	<b>0557 300 105*</b>	100, 500
		28.0	18.0					<b>0557 300 106</b>	100, 500
16.0	blue	24.0	12.0	5.8	0.20	8.8	0.40	<b>0557 300 161*</b>	100, 500
		28.0	18.0					<b>0557 300 162</b>	100, 500
25.0	yellow	30.0	16.0	7.3	0.20	11.2	0.40	<b>0557 300 254*</b>	50, 200
		36.0	22.0					<b>0557 300 255</b>	50
35.0	red	30.0	16.0	8.3	0.20	12.7	0.40	<b>0557 300 351*</b>	50, 200
		39.0	25.0					<b>0557 300 352</b>	50
50.0	blue	36.0	20.0	10.3	0.30	15.0	0.50	<b>0557 300 501*</b>	50
		40.0	25.0					<b>0557 300 502</b>	50

\* Standard length