


Installation accessories for central lubrication parts




Hexagon nut

DIN 936, flat form, old type

galvanized steel, blue passivated (A2K), hardn.: 17H


Thread d	s mm	e mm	m mm	galv. steel, blue pass. Art. No.	Pack Qty.
M 14 x 1.5	22	24.49	8	0319 14 15	100
M 16 x 1.5	24	26.75	8	0319 16 15	50
M 20 x 1.5	30	32.95	9	0319 20 15	



Schnorr lock washer

galvanized steel, blue passivated (A2K)


Nominal dim. M	d ₁ mm	h mm	galv. steel, blue pass. Art. No.	Pack Qty.
6	10	1.2	0493 06	300/1000
8	13	1.4	0493 08	100/1000
14	22	2	0493 014	100
16	24	2.1	0493 016	
20	30	2.4	0493 020	50



Sheet metal screw

according to DIN 7981 (ISO 7049)

Nom. Ø d mm	Length l mm	d _k mm	k mm	galv. steel, blue pass. Art. No. (A2K)	Pack Qty.
4.2	9.5	8.2	3.05	0115 42 95	100/ 1000
4.8	9.5	9.5	3.55	0115 48 95	
4.8	13	9.5	3.55	0115 48 13	



Hexagon head screw

with full length thread, acc. to DIN 933 (ISO 4017)

Thread-Ø d mm	Length l mm	k mm	e mm	s mm	galv. steel 8.8, blue pass. (A2K) Art. No.	Pack Qty.
M 6	20	4	11.05	10	0057 6 20	200/500
	25				0057 6 25	200
	30				0057 6 30	
	35				0057 6 35	
	40				0057 6 40	100/200
	45				0057 6 45	
	55				0057 6 55	100
M 8	25	5.3	14.38	13	0057 8 25	200
	35				0057 8 35	