



Designation	Height mm	Width mm	Length mm	Art. No.	P. Qty.
20 x 20	20	20	500	0973 420 20	36
30 x 30	30	30		0973 430 30	16
40 x 40	40	40		0973 440 40	84

Flexible Wiring Channel

- **Rectangular design → approx. 30% more useable volume compared to round design.**
- **Outstanding installation properties when integrating moveable components (e.g. doors, etc.). For use in tight spaces and corners.**
- **Bottom with double-sided adhesive tape.**

- Simple insertion of wires without additional tools.
- Single row bottom hole pattern (elongated holes 4.5 x 8 mm).
- Material: PVC, self-extinguishing according to UL94 V2, temperature stability to +80°C.
- Colour: grey, similar to RAL 7040.
- Length: 500 mm.



Type	Clamping range mm	Drilling diameter mm	Art. No.	P. Qty.
2/5	approx. 2–5	4	0973 994 25	100
4/7	approx. 4–7		0973 994 47	
3/7	approx. 3–7	6	0973 996 37	

Body-bound rivets

- For riveting of one or more sheets or plates.
- Reusable after undoing.
- Corrosion-proof.
- High insulating effect.
- Quick and uncomplicated attachment method.
- Easy disassembly.
- **Halogen and silicone free.**



Supplementary products

Winding hose, Art. No. 0771 00 ...
 Cable ties, Art. Pre No. 0502
 Body-bound rivets, Art. No. 0500 718
 Spreading tool, Art. No. 0500 100 0..
 Mitre saw, Art. No. 0695 932 192