

## HEAT-SHRINK HOSES



**Shrinkage rate 3:1 with internal adhesive**

• **Shrinkage rate of 3:1**  
→ for bridging large diameter differences.

- Flame-retardant (not adhesive).
- Good electrical, chemical and physical properties.
- Applications: Moisture-resistant insulation of electrical connections, connectors, etc.

Technical Data:	
Shrinking rate	3:1
Temperature range	-55°C to +85°C
Shrinking temperature	> +120°C
Change in length after shrinking	approx. ± 10% max.
Dielectric strength	20 kV/mm



**Version 1,**  
**Length: 100 mm**

Type	Inside dia. in mm	Dimensions after complete shrinkage		Art. No.	P. Qty.
		Inside dia. in mm	Wall thickness approx. mm		
3,0 / 1,0	3,0	1,0	1,00	<b>0771 003 200</b>	50
6,0 / 2,0	6,0	2,0	1,20	<b>0771 006 400</b>	
12,0 / 4,0	12,0	4,0	1,35	<b>0771 012 700</b>	25
24,0 / 8,0	24,0	8,0	2,20	<b>0771 025 400</b>	



**Version 2,**  
**Length: 1,000 mm (cut to length)**



Type	Inside dia. in mm	Dimensions after complete shrinkage		Art. No. gray	Art. No. black	P. m
		Inside dia. in mm	Wall thickness approx. mm			
3,0 / 1,0	3,0	1,0	1,00	<b>0771 003 201</b>	<b>0771 003 202</b>	10
6,0 / 2,0	6,0	2,0	1,20	<b>0771 006 401</b>	<b>0771 006 402</b>	
12,0 / 4,0	12,0	4,0	1,35	<b>0771 012 701</b>	<b>0771 012 702</b>	5
24,0 / 8,0	24,0	8,0	2,20	<b>0771 025 401</b>	<b>0771 025 402</b>	