


COUNTERSUNK WASHERS/WASHERS





For thread	d ₁ in mm	d ₂ in mm	d ₃ in mm	h in mm	Art. No.	P. Qty.	Art. No. Aluminum	P. Qty.
M4	4.3	14	10.5	2.8	0457 54	200	0457 64	200
M5	5.3	16	12	3.2	0457 55	200	0457 65	200
M6	6.4	18	14.5	3.8	0457 56	200	0457 66	200
M8	8.4	25	19	5.0	0457 58	200	0457 68	200


Storable in ORSY® System

For countersunk head screws

- Solid material washers.
- For aluminum window construction, sunroom construction, facade construction, stair construction, tram construction, rail car construction and tram workshops.

RUBBER WASHERS





d in mm	d ₁ in mm	h in mm	Art. No.	P. Qty.
4.0	10	3	0422 4 10	100
6.5	17	2	0422 65 17	100/1000
6.5	20	3	0422 65 20	100
8.0	30	7	04228 30	100
8.7	25	5	0422 87 25	100
11.0	22	12	0422 11 22	100

Storable in ORSY® System

- Used as spacers for sign screw connections.
- Rubber washers are used with soft, rough and untreated or finely finished surfaces.
- Do not cause surface damage.
- Alcohol-resistant.
- Shore hardness A: 70 ± 5 .
- Not ozone-resistant.
- Not suitable for mounting solar roofs.