



Hexagon Bolts

with fine thread DIN 961/ISO 8676

**Steel 10.9, galvanised,
yellow passivated**

Benefits of fine thread:

- Greater self-locking.
- Greater tightening torque.
- Great loadability.

Thread dia. d	M 8x1	M 10x1	M 12x1.5	M 14x1.5	M 16x1.5	M 18x1.5
k in mm	5.3	6.4	7.5	8.8	10	11.5
e in mm	22	26	30	34	38	42
s in mm	13	17	19	22	24	27

Thread dia. d	Thread pitch in mm	l in mm	Steel 10.9, galvanised, yellow passivated Art. No.	P. Qty.
M 8	1.0	20	0067 8 20	100
	1.0	25	0067 8 25	
	1.0	35	0067 8 35	
M 10	1.0	20	0067 10 20	100
	1.0	25	0067 10 25	
	1.0	30	0067 10 30	
	1.0	35	0067 10 35	
	1.0	40	0067 10 40	
M 12	1.5	20	0067 12 20	100
	1.5	25	0067 12 25	
	1.5	30	0067 12 30	
	1.5	35	0067 12 35	
	1.5	40	0067 12 40	
	1.5	45	0067 12 45	
	1.5	50	0067 12 50	
	1.5	60	0067 12 60	50
M 14	1.5	25	0067 14 25	100
	1.5	30	0067 14 30	
	1.5	35	0067 14 35	
	1.5	40	0067 14 40	
	1.5	45	0067 14 45	50
	1.5	50	0067 14 50	
	1.5	55	0067 14 55	
	1.5	65	0067 14 65	
M 16	1.5	30	0067 16 30	50
	1.5	35	0067 16 35	
	1.5	40	0067 16 40	
	1.5	45	0067 16 45	
	1.5	50	0067 16 50	25
	1.5	55	0067 16 55	50
	1.5	60	0067 16 60	25
M 18	1.5	35	0067 18 35	50
	1.5	40	0067 18 40	
	1.5	45	0067 18 45	
	1.5	50	0067 18 50	

