

CABLE CLAMP INSERT CLIP

High pull-out forces



Application area

For fastening of cables NYM 3 x 1.5 or 5 x 1.5 on concrete or solid brick, where normal nail clamps cannot be used.

Instructions

- 5 mm drill hole – knock in the plug clip with a hammer
- 6 mm drill hole – press in the plug clip manually



Min./max. grip range	7-12 mm
Diameter of hole (d)	6 mm
Min./max. temperature resistance	-30 to 80 °C
Colour	Light grey RAL 7035
Material	PA - Polyamide
Halogen-free	Yes
Silicone-free	Yes

Art. No.	0593 503	0593 504
P. Qty.	200	100
Version	One side	Both sides
Width	17.5 mm	27 mm

Can be stored in ORSY system



<STEPREF A="AT_PublicationShortTextUSP"
O="CL01_5504011802"
OT="Product" VC="1401_en"
VO="1406080" W="Main" />

Art. No.	0971 100 985
P. Qty.	200
Suitable for cable ties	max. 8.5 mm
Drill hole diameter	6 mm
Min./max. temperature conditions	-25 to 40 °C
Material	PP - Polypropylene
Halogen-free	Yes
Silicone-free	Yes

<STEPREF A="AT_PublicationPackaging" O="CL01_5504011802" OT="Product" VC="1401_en"
VO="1406080" W="Main" />