

DRIVE-IN ANCHOR W-ED/A4 – W-ED/HCR

13.2

Anchor dimensions, drive-in anchor W-ED/A4, stainless steel A4



Description	Anchor dia.	Total length L _H [mm]	Drill bit nominal dia. d ₀ [mm]	Drill hole depth h ₀ ≥ [mm]	Thread depth (max. screw-in depth) L _{th} [mm]	Minimum screw-in depth L _{smin} [mm]	Art. No.	P.Qty.
W-ED/A4	M6	30	8	30	13	7	0904 030 06	100
	M8	30		30	13	9	0904 030 08	
		40	40	20	9	0904 030 081		
	M10	40	12	40	15	11	0904 030 10	50
	M12	50	15	50	18	13	0904 030 12	
	M16	65	20	65	23	18	0904 030 16	25
M20	80	25	80	34	22	0904 030 20*		

* S-24 cannot be ordered.

Marking/spreading tool with hand guard (visual setting check)



for drive-in anchors	Art. No.	P.Qty.
M8 x 30	0904 022 08	1
M8 x 40	0904 022 081	
M10 x 40	0904 022 10	
M12 x 50	0904 022 12	
M16 x 65	0904 022 16	
M20 x 80	0904 022 20	

Spreading tool (no visual setting check)



for drive-in anchors	Art. No.	P.Qty.
M6 x 30	0904 020 06	1
M8 x 30	0904 020 08	
M8 x 40	0904 020 081	
M10 x 40	0904 020 10	
M12 x 50	0904 020 12	
M16 x 65	0904 020 16	
M20 x 80	0904 020 20	

Machine setting tool (no visual setting check)



for drive-in anchors	Art. No.	P.Qty.
M8 x 30	0904 023 08	1
M10 x 40	0904 023 10	
M12 x 50	0904 023 12	