# PLUG CLAMPS

**Bracket Clamp** Individual and bundle mounting

**Double Clamp**

**Mounting of individual lines, bundled lines and flexible plastic pipes (Art. No. 0975 2...) on the surface or in wall slits.**

- Suitable for concrete, solid sand-lime brick, lightweight concrete, solid clinker and natural stone.
- Drill, insert, you're done!
- High pull-out values (up to 40 kg).
- One-hand installation.
- High material quality and strength.
- Temperature-resistance: –20°C to +85°C.
- Color: Gray (RAL 7035).
- **Halogen- and silicone-free.**
- Material: Polypropylene, UV-stabilized.

| Appearance | Designation | Drilled hole dia. in mm | Clamping range dia. in mm | Art. No. | P. Qty. |
|---|---|---|---|---|---|
| | Bracket Clamp for individual cables | 6 | 3 – 13 | **0971 100 313** | 200/1,500 |
| | | 6 | 6 – 20 | **0971 100 620** | 200 |
| | | | | | |
| | Bracket Clamp for cable bundles and flexible tubes | 6 | 8 – 28 | **0971 100 828** | 200/500 |
| | | 6 | 20 – 40 | **0971 100 240** | 200 |
| | | | | | |
| | Double Clamp for two parallel individual cables | 6 | 4 – 12 | **0971 100 412** | 200 |
| | | | | | |

**Storable in ®ORSY**

# ANCHOR PLUG

**For mounting cable ducts (Art. No. 0973 6...) "with a flick of your thumb". Without tools and without screws.**

- Suitable for concrete, solid sand-lime brick, lightweight concrete, solid clinker and natural stone.
- Drill, insert, you're done!
- High pull-out values (up to 40 kg).
- One-hand installation.
- High material quality and strength.
- Temperature-resistance: –20°C to +85°C.
- Color: Gray (RAL 7035).
- **Halogen- and silicone-free.**
- Material: UV-stabilized polyamide.

| Appearance | Drill hole dia. | Head dimensions/ length in mm | Art. No. | P. Qty. |
|---|---|---|---|---|
|  | 6 | 14 x 10 x 33 | **0971 500 031** | 200 |
| | 6 | 14 x 10 x 40 | **0971 500 040** | 150 |
| | 6 | 14 x 10 x 50 | **0971 500 049** | 100 |

**Storable in ®ORSY**

MWF - 09/10 - 02106 - ©