

CABLE GLAND

Metric EN 60423 / EN 62444

Material	Brass, galvanised nickel-plated
Sealing ring	Polychloroprene nitrile rubber CR/NBR, halogenic
Disk insert	Polyamide PA6 V-2
O-ring connection thread	Nitrile rubber NBR
Temperature range	-20°C to +100°C
Protection rating	IP68 – 5 bar



	Threaded connection	Cable dia. mm (clamping range)	Thread length mm	Width across flats mm	Art. no.	PU qty.
	M12 x 1.5	3-6	5	14	0967 760 12	100
	M16 x 1.5	5-9	5	17	0967 760 16	
	M20 x 1.5	9-13	6	22	0967 760 20	
	M25 x 1.5	11-16	7	27	0967 760 25	
	M32 x 1.5	14-21	8	34	0967 760 32	25
	M40 x 1.5	19-27	8	43	0967 760 40	10
	M50 x 1.5	24-35	9	55	0967 760 50	5
	M63 x 1.5	32-42	10	65	0967 760 63	
	M63 x 1.5	38-48	10	65	0967 760 631	

Can be stored in ORSY® system

COUNTER NUT

Metric EN 60423

Material	Brass, galvanised nickel-plated
Temperature range	Up to +200°C

	Threaded connection	Height mm	Width across flats mm	Art. no.	PU qty.
	M12 x 1.5	2.8	15	0967 770 12	100
	M16 x 1.5	2.8	19	0967 770 16	
	M20 x 1.5	3	24	0967 770 20	
	M25 x 1.5	3.5	30	0967 770 25	
	M32 x 1.5	4	36	0967 770 32	50
	M40 x 1.5	5	46	0967 770 40	
	M50 x 1.5	5	60	0967 770 50	
	M63 x 1.5	6	70	0967 770 63	

Can be stored in ORSY® system