

282081-1


✓ ACTIVE

AMP | AMP Superseal 1.5mm Series

TE Internal #: 282081-1
Cavity Blanking Plug, Silicone, Red, 5.5 mm [.217 in] Cavity
Diameter, -40 - 130 °C [-40 - 266 °F] Operating Temperature, AMP
Superseal 1.5mm Series
[View on TE.com >](#)



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: **Cavity Blanking Plug**
Primary Product Material: **Silicone**
Primary Product Color: **Red**
Cavity Diameter: **5.5 mm [.217 in]**
Resistance to Hydrocarbons: **Poor**

Features

Product Type Features

Connector Seal & Plug Type	Cavity Blanking Plug
----------------------------	----------------------

Body Features

Primary Product Material	Silicone
Primary Product Color	Red

Dimensions

Cavity Diameter	5.5 mm[.217 in]
-----------------	-----------------

Usage Conditions

Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C [149 °F][158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]
Operating Temperature Range	-40 - 130 °C[-40 - 266 °F]

Industry Standards

UL Flammability Rating	None
------------------------	------

Other

Resistance to Hydrocarbons	Poor
Shore A Hardness	50
Contains Lubricant	Yes