

ORSY	mm ²	Size in mm	Locking lug	Material	Surface	Art. No.	P. Qty.
	0.5 - 1.5	6.3 x 0.8	-	CuZn	Sn (tinned)	0558 160 77	100
	2.5 - 4.0					0558 160 78	
	4.0 - 6.0					0558 160 79	
	1.5 - 2.5			CuSn	Ag (silver-plated)	0558 160 71	50
	Housing, black, for Art. No. 0558 160 71 - 0558 160 79					0558 101 1	100

Additional products – recommendation:

Releasing Tool for Push-On Receptacles with locking lug

Art. No. 0713 558 2..

Push-On Tabs

ORSY	mm ²	Size in mm	Locking lug	Hole dia. in mm	Material	Surface	Art. No.	P. Qty.
	1.0 - 1.5	2.8 x 0.5	1 x	1.2	CuZn	bright	0558 505 41	100
	0.5 - 1.0	2.8 x 0.8	-	1.2			0558 514 4	
	0.5 - 1.0	6.3 x 0.8	-	1.65			0558 513 5	
	1.5 - 2.5	6.3 x 0.8	-	1.65			0558 501 9	
	1.5 - 2.5	6.3 x 0.8	1 x	-		0558 505 4	100/300	
	0.75 - 2.0	5.1 x 0.8	1 x	-		0558 994 6	100	
	0.5 - 1.0	6.3 x 0.8	1 x	1.65		0558 996 0		
	1.5 - 2.5	6.3 x 0.8	1 x	-		0558 991 8		
	4.0 - 6.0	6.3 x 0.8	1 x	1.65		0558 996 3		
	0.5 - 2.0	6.0 x 0.8	-	2.00		0558 190 26		
	0.8 - 2.5	6.3 x 0.8	1 x	1.65		0558 993 7		
	1.5 - 2.5	6.3 x 0.8	1 x	1.65		0558 993 5		
	4.0 - 6.0	6.3 x 0.8	1 x	-		0558 993 4		

Additional products – recommendation:

Releasing Tool for Push-On Tabs with locking lug

Art. No. 0713 558 2..

Additional Products

ORSY	Designation	Art. No.	P. Qty.
	Insulating grommet, transparent PE, for push-on receptacles, plug width 6.3 mm, cable gland: 2.5 mm dia.	0558 180 9	100
	Insulating grommet, transparent PE, for flat plugs, plug width 6.3 mm, cable gland: 2.5 mm dia.	0558 181 01	
	Insulating grommet, transparent PE, for push-on receptacles, plug width 6.3 mm, cable gland: 4.0 x 2.8 mm	0558 180 09	
	Insulating grommet, transparent PE, for flat plugs, plug width 6.3 mm, cable gland: 4.0 x 2.8 mm	0558 181 0	