

BATTERY CHARGER PRO 4



Art. No.	0827 405
P. Qty.	1
Min./max. input voltage	100-240 V/AC
Input voltage 2	12 V/DC
Charging voltage per battery	1.45 V/DC
Zero-watt technology	No
Charging current at USB output	1000 mA
Maximum number of charging slots for AAA batteries	4 PCS
Charging current for AAA battery	450 mA
Maximum number of charging slots for AA batteries	4 PCS
Charging current for AA battery	450 mA
Safety timer	Yes
Display	LCD
Individual slot monitoring	Yes
Overload protection (trickle charging)	Yes
Rechargeable battery defect detection	Yes
Temperature monitoring	No
Automatic refresh function	No
Quick test for capacity	No
Length x width x height	105 x 65 x 27 mm
Voltage shutdown	Yes
Product weight (per item)	487.000 g
IP protection class	IP 20

Contents for Art. No.	Designation	Art. No.	Number
0827 405	Pre-charged NiMH battery	0827 311	4
	Pre-charged NiMH battery	0827 312	4

Includes pre-charged NiMH batteries (4 x AAA and 4 x AA)

Enhanced safety for the user

- Battery defect detection
- Alkaline detection
- Inverse-polarity protection
- Multiple overload protection

Suitable for use with conventional batteries

Trickle charging

Clear LC display

- Graphic display
- Intuitive operation

USB output

Any devices that can be charged via USB are compatible – e.g. PDAs, MP3 players, portable games consoles, navigation devices and mobile phones.

Suitable for use on the go and anywhere in the world

- Long-range input 100–240 V/AC
- Includes 12-V/DC vehicle mains plug

Application area

For 1-4 Micro AAA/Mignon AA batteries or a device that can be charged via USB