

CLAMPING SLEEVES

Nominal dia. d in mm	I in mm	s in mm	a in mm	d ₁ in mm	Bare steel Art. No.	P. Qty.
20	50	4	3.4	12.5	0475 20 50	25
20	55	4	3.4	12.5	0475 20 55	25
20	70	4	3.4	12.5	0475 20 70	25/50
20	80	4	3.4	12.5	0475 20 80	10
20	90	4	3.4	12.5	0475 20 90	10
20	95	4	3.4	12.5	0475 20 95	25
20	100	4	3.4	12.5	0475 20 100	10
20	120	4	3.4	12.5	0475 20 120	10
20	140	4	3.4	12.5	0475 20 140	5
20	160	4	3.4	12.5	0475 20 160	25
20	180	4	3.4	12.5	0475 20 180	5
20	200	4	3.4	12.5	0475 20 200	10
21	18	4	3.4	13.5	0475 21 18	100
21	40	4	3.4	13.5	0475 21 40	10
21	55	4	3.4	13.5	0475 21 55	25
21	75	4	3.4	13.5	0475 21 75	25
21	90	4	3.4	13.5	0475 21 90	25
21	95	4	3.4	13.5	0475 21 95	5/25
21	120	4	3.4	13.5	0475 21 120	10
21	140	4	3.4	13.5	0475 21 140	10
21	160	4	3.4	13.5	0475 21 160	10
21	180	4	3.4	13.5	0475 21 180	10
21	200	4	3.4	13.5	0475 21 200	10
25	40	5	3.4	15.5	0475 25 40	10
25	50	5	3.4	15.5	0475 25 50	25
25	60	5	3.4	15.5	0475 25 60	10

ISO 8752

Nominal dia. d in mm	I in mm	s in mm	a in mm	d ₁ in mm	Bare steel Art. No.	P. Qty.
25	80	5	3.4	15.5	0475 25 80	10
25	85	5	3.4	15.5	0475 25 85	10
25	100	5	3.4	15.5	0475 25 100	10/25
25	120	5	3.4	15.5	0475 25 120	10
25	140	5	3.4	15.5	0475 25 140	10
25	150	5	3.4	15.5	0475 25 150	10
25	175	5	3.4	15.5	0475 25 175	10
25	180	5	3.4	15.5	0475 25 180	10
28	40	5.5	3.4	17.5	0475 28 40	10
28	50	5.5	3.4	17.5	0475 28 50	1/50
28	55	5.5	3.4	17.5	0475 28 55	10
30	60	6	3.4	18.5	0475 30 60	10
30	75	6	3.4	18.5	0475 30 75	10
30	110	6	3.4	18.5	0475 30 110	25
30	120	6	3.4	18.5	0475 30 120	10
30	140	6	3.4	18.5	0475 30 140	10
30	200	6	3.4	18.5	0475 30 200	10
35	80	7	3.4	21.5	0475 35 80	10
40	40	7.5	4.6	25.5	0475 40 40	25
40	75	7.5	4.6	25.5	0475 40 75	5
40	120	7.5	4.6	25.5	0475 40 120	10/25
40	140	7.5	4.6	25.5	0475 40 140	10
40	150	7.5	4.6	25.5	0475 40 150	1
40	160	7.5	4.6	25.5	0475 40 160	1
40	175	7.5	4.6	25.5	0475 40 175	10