

SET SCREWS

DIN EN ISO 4026

replaces DIN 913

with Allen socket and truncated cone

A2 stainless steel, 21 H
A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of 210 HV.

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M10	18	0261 10 18	100	0221 10 18	100
	20	0261 10 20		0221 10 20	
	25	0261 10 25		0221 10 25	
	30	0261 10 30		0221 10 30	
	35	0261 10 35		0221 10 35	
	40	0261 10 40		0221 10 40	
	45	0261 10 45		0221 10 45	
	50	0261 10 50		0221 10 50	
	55	0261 10 55			
	60	0261 10 60		0221 10 60	
	70	0261 10 70			
	80	0261 10 80	50	0221 10 80	
	90	0261 10 90			
	100			0221 10 100	
M12	12	0261 12 12	50	0221 12 12	50
	16	0261 12 16		0221 12 16	
	20	0261 12 20		0221 12 20	
	25	0261 12 25		0221 12 25	
	30	0261 12 30		0221 12 30	
	35	0261 12 35		0221 12 35	
	40	0261 12 40		0221 12 40	
	45	0261 12 45		0221 12 45	
	50	0261 12 50		0221 12 50	
	55	0261 12 55		0221 12 55	
	60	0261 12 60		0221 12 60	
	70	0261 12 70			
	80	0261 12 80		0221 12 80	
	90	0261 12 90			
	100	0261 12 100			
M16	16	0261 16 16	100	0221 16 16	100
	20	0261 16 20			
	25	0261 16 25			
	30	0261 16 30			
	35			0221 16 35	100
	40	0261 16 40			
	45	0261 16 45			
	50	0261 16 50		0221 16 50	50
	55			0221 16 55	
	60	0261 16 60	50		
	90	0261 16 90	50		

Can be stored in ORSY®

DIN 913 has been retracted and replaced by international standard DIN EN ISO 4026.