

## WAGO MICRO PUSH-WIRE CONNECTOR, SCREWLESS



Illustration only



### Stackable

Testing port for voltage tester

### Application area

Connection terminal for single-wire copper conductors.

For low-current installations: Communication, ringer, alarm and signalling systems (VdS 2116). For EIB applications.

<b>Min./max. wire diameter</b>	0.6-0.8 mm
<b>Min./max. wire-stripping length</b>	5-6 mm
<b>Nominal current</b>	6 A
<b>Nominal voltage</b>	100 V
<b>Max. ambient temperature</b>	60 °C
<b>Flammability</b>	Self-extinguishing in accordance with UL94 V0
<b>Material of the housing</b>	Polyamide 6.6

Number of ladders	Colour	Art. No.	P. Qty.
4 PCS	Dark grey	<b>0556 004</b>	100
4 PCS	Light grey (bright grey)	<b>0556 003</b>	100
4 PCS	Red	<b>0556 002</b>	100
4 PCS	Yellow	<b>0556 001</b>	100
8 PCS	Dark grey	<b>0556 008</b>	100
8 PCS	Light grey (bright grey)	<b>0556 007</b>	100
8 PCS	Red	<b>0556 006</b>	100
8 PCS	Yellow	<b>0556 005</b>	100

Compatible with ORSY® storage system

Related products	Art. No.
Wire stripping pliers	<b>0714 108 10</b>
Automatic self-adjusting wire stripping pliers	<b>0714 109 010</b>
Two-pin voltage tester Multi-Tester Pro II LCD	<b>0715 53 175</b>

## TELECOMMUNICATIONS CONNECTORS



Illustration only

For single-wire copper conductors

### Cut-and-clamp technology

No stripping – saves time

### Contact paste (sealing gel)

High-quality connection

### Application area

Connection terminal for single-wire copper conductors.

For low-current installations: communication, ringer, alarm and signalling systems.

<b>Art. No.</b>	<b>0556 011</b>	<b>0556 010</b>	<b>0556 012</b>
<b>P. Qty.</b>	100	100	100
<b>Number of ladders</b>	2 PCS	2 PCS	3 PCS
<b>Min./max. strand diameter</b>	0.4-0.7 mm	0.4-0.7 mm	0.4-0.9 mm
<b>Max. diameter of insulation</b>	1.27 mm	1.52 mm	1.67 mm

Can be stored in ORSY system

Related products	Art. No.
VDE combination pliers DIN ISO 5746 IEC 60900	<b>0714 01 575</b>