

## S 2-A BATTERY-OPERATED SCREWDRIVER



**Handy and compact battery-operated unit with two speeds for screwing in and drilling.**

**With two 2.4-volt batteries and charger in case**  
**Art. No. 0700 101 2**

**In box, without charger or rechargeable batteries**  
**Art. No. 0700 101 0**

**Driver can be used either straightened or angled.**

Unit can also be used in tight spots which are hard to access.

**2-speed gear unit**

15 torque levels and one drilling level enable proper setting for the respective screwing or drilling case.

**Switch-on lock**

Prevents the driver from being switched on inadvertently.

**Direct bit mount**

Thanks to the short design, bit holders or long bits can be inserted directly.

**3-year guarantee**

On manufacturing and material defects

Scope of delivery			
Designation	Art. No.	P. Qty. Art. No. 0700 101 2	P. Qty. Art. No. 0700 101 0
S 2-A Battery-Operated Screwdriver	<b>0700 101 X</b>	1	1
Battery, 2.4 V	<b>0700 970 013</b>	2	-
AL 60-S2 Charger	<b>0700 870</b>	1	-

Technical data			
Voltage	V	2.4	
Battery capacity	Ah	1.3	
Idling speed 1st/2nd speed	rpm	170/350	
Maximum torque	in Nm	2.7	
Mount		1/4"  C 6.3/E6.3	
Weight of machine without battery approx.	in kg	0.4	
Weight of individual battery approx.	in kg	0.1	
Extended length	in mm	260	
Diameter	in mm	39	



Straightened



Angled

### Accessories

1/4" PH 1-2 Bit, E 6.3, length: 73 mm  
**Art. No. 0614 176 774-775**

1/4" PZ 1-2 Bit, E 6.3, length: 73 mm  
**Art. No. 0614 176 776-777**



1/4" Slotted Bit, E6.3, length: 73 mm  
**Art. No. 0614 175 660-663**



1/4" Magnetic Bit Holder, E 6.3, length: 74 mm  
**Art. No. 0614 176 702**

1/4" Non-magnetic Bit Holder, E 6.3, length: 74 mm  
**Art. No. 0614 176 729**



1/4" Mini Chuck  
**Art. No. 0713 92 04**

