



FBS WINDOW CONSTRUCTION SCREWS



FBS

Steel, galv. (thick-film passivation), Deltacoll-coated
Steel, galv., blue passivated (A3K)
Steel, yellow galvanized (A3L)
Steel, galv., KTL, black coated

- Drive: PH2/AW20.
 - Special thread with needle tip
 - Head dia.: 7.0 mm
 - Increased corrosion protection due to thick-film passivation and Deltacoll-coating or KTL black (duplex process).
In the salt-spray mist test according to DIN EN ISO 9227-NSS, 240 hours without red rust on base metal corrosion.
 - Heat-resistance of the corrosion-protection coating: 150°C.
- Cr(VI)-free corrosion-protection coating.**

Drive	Nominal dia. in mm	Length l in mm	Art. No. Steel, galv. and Deltacoll- coated	Art. No. Steel, galv. and blue passivated	Art. No. Steel, yellow galvanized	Art. No. Steel, galv. and KTL black	P. Qty.
PH2	4.1	19	0185 244 119	0185 284 119	0185 214 119	0185 224 119	1,000
		22	0185 244 122	0185 284 122	0185 214 122	0185 224 122	
		25	0185 244 125	0185 284 125	0185 214 125	0185 224 125	
		30	0185 244 130	0185 284 130	0185 214 130	0185 224 130	
		35	0185 244 135	0185 284 135	0185 214 135	0185 224 135	
		38	0185 244 138	0185 284 138	0185 214 138	0185 224 138	
		45	0185 244 145	0185 284 145	0185 214 145	0185 224 145	500
		50	0185 244 150	–	–	–	
		55	0185 244 155	–	–	–	
		60	0185 244 160	–	–	–	
AW20	4.1	16	0188 144 116	–	–	–	6,000
		19	0188 144 119	–	–	–	5,000
		22	0188 144 122	–	–	–	4,500
		25	0188 144 125	–	–	–	4,000
		30	0188 144 130	–	–	–	2,500
		35	0188 144 135	–	–	–	2,000
		38	0188 144 138	–	–	–	2,000
		45	0188 144 145	–	–	–	1,500
		50	0188 144 150	–	–	–	1000
		55	0188 144 155	–	–	–	
		60	0188 144 160	–	–	–	

Can be stored in ORSY® System.

FBS 1, roller-sorted – For use in automatic machines

Drive	Nominal dia. in mm	Length l in mm	Art. No. Steel, galv. and Deltacoll- coated	P. Qty.
PH2	4.1	19	0185 294 119	5,000
		22	0185 294 122	4,500
		25	0185 294 125	4,000
		30	0185 294 130	2,500
		35	0185 294 135	2,000

Can be stored in ORSY® System.

Please also observe the information
on the overview page.