



Blind Rivet Standard Truss Head

Rivet sleeve: AlMg 2.5

Rivet drift:
steel, galvanised, blue passivated
(A2K)

Standard rivet range

Advantages

High quality rivet joints.

- Clean, solid formation of closing head.
- Reliable, patented rivet drift locking.
- Constant high tensile and shearing strength.
- High-strength rivet joints, impact-resistant and splash-water proof.
- No kinking of rivet sleeve at small nominal clamping areas.

d x l mm	Bore-hole Ø mm	Clamping range mm	dk mm	k mm	dm mm	Shear break load N	Tensile break load N	Art. No.	Pack Qty.
2.4 x 4.0	2.5	0.5 – 2.0	4.8	0.9	1.5	390	580	0936 24 4	1000
2.4 x 6.0	2.5	2.0 – 4.0	4.8	0.9				0936 24 6	1000
2.4 x 8.0	2.5	4.0 – 6.0	4.8	0.9				0936 24 8	1000
3.0 x 4.0	3.1	0.5 – 1.5	6.4	1.1	1.8	600	960	0936 3 4	500
3.0 x 6.0	3.1	1.5 – 3.5	6.4	1.1				0936 3 6	500
3.0 x 8.0	3.1	3.5 – 5.5	6.4	1.1				0936 3 8	500
3.0 x 10.0	3.1	5.5 – 7.0	6.4	1.1				0936 3 10	500
3.0 x 12.0	3.1	7.0 – 9.0	6.4	1.1				0936 3 12	500
3.0 x 16.0	3.1	9.0 – 13.0	6.4	1.1				0936 3 16	500
3.0 x 20.0	3.1	13.0 – 17.0	6.4	1.1				0936 3 20	500
3.0 x 25.0	3.1	17.0 – 22.0	6.4	1.1				0936 3 25	250
3.2 x 6.0	3.3	0.5 – 3.5	6.4	1.1				1.8	800
3.2 x 8.0	3.3	3.5 – 5.5	6.4	1.1	0936 32 8	500			
3.2 x 10.0	3.3	5.5 – 7.5	6.4	1.1	0936 32 10	500			
4.0 x 6.0	4.1	0.5 – 3.0	8.0	1.4	2.1	1300	1500	0936 4 6	500
4.0 x 8.0	4.1	3.0 – 5.0	8.0	1.4				0936 4 8	500
4.0 x 10.0	4.1	5.0 – 6.5	8.0	1.4				0936 4 10	500
4.0 x 12.0	4.1	6.5 – 8.5	8.0	1.4				0936 4 12	500
4.0 x 16.0	4.1	8.5 – 12.5	8.0	1.4				0936 4 16	500
4.0 x 20.0	4.1	12.5 – 16.5	8.0	1.4				0936 4 20	500
4.0 x 25.0	4.1	16.5 – 21.5	8.0	1.4				0936 4 25	500
4.8 x 8.0	4.9	3.0 – 4.5	9.6	1.6				2.6	1800
4.8 x 10.0	4.9	4.5 – 6.0	9.6	1.6	0936 48 10	500			
4.8 x 16.0	4.9	6.0 – 12.0	9.6	1.6	0936 48 16	500			
4.8 x 26.0	4.9	19.1 – 22.2	9.6	1.6	0936 48 26	250			
4.8 x 30.0	4.9	21.3 – 26.4	9.6	1.6	0936 48 30	250			
4.8 x 40.0	4.9	20.0 – 34.0	9.6	1.6	0936 48 40	250			
4.8 x 45.0	4.9	35.0 – 40.0	9.6	1.6	0936 48 45	250			

