

W-ID INSULATING ANCHOR

74.1

W-ID Set **galvanized steel**

Art. No. 0903 500 96



Delivery scope:

- W-ID 95
- Cover rosette in PA6
- PVC hose, 12.0 x 65 mm
- Stud bolt, M10 x 120 mm, galvanized
- TX 25 bit

Additional accessories for screwing in the anchor:

Setting tool: Screwing tool Art. No. 0715 137 10 + Adapter

Art. No. 0614 176 780

Combination wrench Art. No. 0713 301 08

W-ID set **stainless steel A2**

Art. No. 0903 500 97



Delivery scope:

- W-ID 95
- Cover rosette in PA6
- PVC hose, 12.0 x 65 mm
- Stud bolt, M10 x 120 mm, A2

Required accessories for screwing in the anchor:

Setting tool: Screwing tool Art. No. 0715 137 10 + Adapter

Art. No. 0614 176 780 or

Combination wrench Art. No. 0713 301 08

Characteristic values

Performance Data				
Anchors			50	95
Recom. load	Styrofoam \geq PS 20	$F_{recom.}$ [kN]	0.04	0.08
	PUR 30 hard foam		0.12	0.20
Axial spacing	$s \geq$ [mm]		150	300
Edge spacing	s_e [mm]		75	150
Setting depth	h_s [mm]		50	95
Minimum component thickness	$t \geq$ [mm]		50	95
Thread dia. of screw	d_{thr} [mm]		4-5/M4	8/M8 ¹
Nom. drill dia.	d_{dr} [mm]		w/o predrilling	
Hole dia. in comp.	d_{com} [mm]		4.5-5.5	8.5 or 4.5-5.5
Drilled hole dia. in plaster or cladding sheet metal	t [mm]		18	30

¹With Art. No. 0903 8 40 the screw diameter can be reduced to 4-5; for an M8 screw, screw at least 35 mm into the anchor.

Anchor Dimensions				
Total length	l [in mm]	50	95	
Max. screw-in depth of screw	d_a [mm]	40	70	
Designation		W-ID	W-ID	W-ID Set galvanized steel
Art. No.		0903 500 50*	0903 500 95*	0903 500 96*
Designation		-	-	W-ID set stainless steel A2
Art. No.		-	-	0903 500 97*
Art. No. Setting tool, Steel galv./yellow chrom. P. Qty. = 1		0903 500	0057 8 30*	
Packing unit	P. Qty.	100	25	20
Cover rosette (gray)	Art. No. P. Qty. = 10	0903 500 99		

*Storable in ORSY® System

Würth System Components

