

SET SCREWS

DIN EN ISO 4029

replaces DIN 916

with Allen socket and cup point

Bare steel, 45 H
Galvanized steel, blue passivated (A2K), 45 H

Hardness 45H corresponds to a hardness of 450 HV.

Nominal dia.	Length l in mm	Bare steel Art. No.	P. Qty.	Galvanized steel Blue-passivated Art. No.	P. Qty.
M8	70	0254 8 70	100		
	80	0254 8 80			
	90	0254 8 90			
	100			0254 08 100	100
M10	8	0254 10 8	100	0254 010 8	100
	10	0254 10 10		0254 010 10	
	12	0254 10 12		0254 010 12	
	16	0254 10 16		0254 010 16	
	20	0254 10 20		0254 010 20	
	25	0254 10 25		0254 010 25	
	30	0254 10 30		0254 010 30	
	35	0254 10 35		0254 010 35	
	40	0254 10 40		0254 010 40	
	45	0254 10 45			
	50	0254 10 50		0254 010 50	
	60	0254 10 60		0254 010 60	
	70	0254 10 70	50	0254 010 70	50
	80	0254 10 80		0254 010 80	
M12	10	0254 12 10	100		100
	12	0254 12 12		0254 012 12	
	16	0254 12 16		0254 012 16	
	20	0254 12 20		0254 012 20	
	25	0254 12 25		0254 012 25	
	30	0254 12 30		0254 012 30	
	35	0254 12 35		0254 012 35	
	40	0254 12 40		0254 012 40	
	50	0254 12 50		0254 012 50	
	60	0254 12 60		0254 012 60	
	70	0254 12 70		0254 012 70	
	80	0254 12 80	50		
	90	0254 12 90			
M16	16	0254 16 16	50	0254 016 16	50
	20	0254 16 20		0254 016 20	
	25	0254 16 25	25	0254 016 25	25
	30	0254 16 30		0254 016 30	
	35			0254 016 35	
	40	0254 16 40	100	0254 016 40	
	45	0254 16 45		0254 016 45	
	50	0254 16 50		0254 016 50	
	60	0254 16 60	10	0254 016 60	10
	70	0254 16 70		0254 016 70	
	80	0254 16 80	50	0254 016 80	
	90	0254 16 90		0254 016 90	
	100	0254 16 100			

Can be stored in ORSY®

DIN 916 has been retracted and replaced by international standard DIN EN ISO 4029.