

SET SCREWS

DIN EN ISO 4027

replaces DIN 914

with Allen socket and flattened tip

A2 stainless steel, 21 H
A4 stainless steel, 21 H



Hardness 21H corresponds to a hardness of 210 HV.

The standard version of the tip is 90°, but very short lengths (those marked with an *) have an angle of 120°.

Nominal dia. d	Length l in mm	A2 stainless steel Art. No.	P. Qty.	A4 stainless steel Art. No.	P. Qty.
M5	5*	0262 5 5	100	0269 5 5	200
	6*	0262 5 6		0269 5 6	
	8	0262 5 8		0269 5 8	
	10	0262 5 10		0269 5 10	
	12	0262 5 12		0269 5 12	
	14	0262 5 14			
	16	0262 5 16		0269 5 16	
	20	0262 5 20		0269 5 20	
	25	0262 5 25		0269 5 25	
	30	0262 5 30		0269 5 30	
	35	0262 5 35		0269 5 35	
	40	0262 5 40		0269 5 40	
	50	0262 5 50			
M6	5*	0262 6 5	100		200
	6*	0262 6 6		0269 6 6	
	8	0262 6 8		0269 6 8	
	10	0262 6 10		0269 6 10	
	12	0262 6 12		0269 6 12	
	14	0262 6 14			
	16	0262 6 16		0269 6 16	
	18	0262 6 18			
	20	0262 6 20		0269 6 20	
	25	0262 6 25		0269 6 25	
	30	0262 6 30		0269 6 30	
	35	0262 6 35		0269 6 35	
	40	0262 6 40		0269 6 40	
	45	0262 6 45			
	50	0262 6 50		0269 6 50	
	60	0262 6 60			
M8	6*	0262 8 6	100		100
	8*	0262 8 8		0269 8 8	
	10	0262 8 10		0269 8 10	
	12	0262 8 12		0269 8 12	
	14	0262 8 14			
	16	0262 8 16		0269 8 16	
	20	0262 8 20		0269 8 20	
	25	0262 8 25		0269 8 25	
	30	0262 8 30		0269 8 30	
	35	0262 8 35		0269 8 35	
	40	0262 8 40		0269 8 40	
	45	0262 8 45		0269 8 45	
	50	0262 8 50		0269 8 50	
	60	0262 8 60			

*Angle of the flattened tip is 120°.

Can be stored in ORSY®

DIN 914 has been retracted and replaced by international standard DIN EN ISO 4027.