

SCREW WITH FLATTENED HALF ROUND HEAD

ISO 7380-2

with hexagon socket and flange

Nominal Dia. d	Length l mm	Plain steel 010.9 Art. no.	PU/Qty.	Galv. steel 010.9, blue-passivated Art. no.	PU/Qty.	Galv. steel 010.9, black-passivated Art. no.	PU/Qty.	A2 Art. no. 	PU/Qty.
10	10			0060 001 010	200				
	12			0060 001 012	100			0098 021 012	100
	16	0060 031 016	200	0060 001 016	100			0098 021 016	100
	20	0060 031 020	100	0060 001 020	100			0098 021 020	100
	25	0060 031 025	100	0060 001 025	100	0060 010 25	100	0098 021 025	100
	30	0060 031 030	100	0060 001 030	100			0098 021 030	100
	35	0060 031 035	100	0060 001 035	100			0098 021 035	100
	40	0060 031 040	100	0060 001 040	100			0098 021 040	100
	45			0060 001 045	100			0098 021 045	100
	50			0060 001 050	100				
	55	0060 031 055	100						
	60	0060 031 060	100						
	70	0060 031 070	100	0060 001 270	100				
	90			0060 001 290	100				
	100								
	105								
	110								
	150								
12	20	0060 031 220	100	0060 001 220	100				
	25	0060 031 225	100	0060 001 225	100				
	30	0060 031 230	100	0060 001 230	100			0098 021 230	100
	35	0060 031 235	100	0060 001 235	100				
	40	0060 031 240	100	0060 001 240	100			0098 021 240	100
	45			0060 001 245	100			0098 021 245	100
	50	0060 031 250	100	0060 001 250	100				
	55			0060 001 255	100				
	60			0060 001 260	100			0098 021 260	200
	70	0060 031 270	100					0098 021 290	50

Can be stored in ORSY® system



ORSY® 200 assortment
ISO 7380-2
Screw with flattened
half round head
with hexagon socket and flange
010.9 galvanised steel
blue passivated (A2K)
Art. no. 0964 060
 PU/Qty. 1

Nominal dia. mm	Length l mm	Art. no.	PU Qty.	Nominal dia. mm	Length l mm	Art. no.	PU Qty.
M 4	6	0060 004 6	100	M 6	10	0060 006 10	100
	8	0060 004 8			12	0060 006 12	
	10	0060 004 10			16	0060 006 16	
	12	0060 004 12			20	0060 006 20	
	16	0060 004 16			25	0060 006 25	
M 5	8	0060 005 8	50	M 8	10	0060 008 10	50
	10	0060 005 10			12	0060 008 12	
	12	0060 005 12			16	0060 008 16	
	16	0060 005 16			20	0060 008 20	
	20	0060 005 20			25	0060 008 25	

Can be stored in ORSY® system