

CUT PROTECTION GLOVE W-200 LEVEL C



Gauge	13
Material of the liner	Dyneema®/polyamide/glass
Material coating	Polyurethane
EN standard	388, 420
Cut resistance according to ISO 13997	C
Category	II

Size	Art. No.	P. Qty.
7	0899 400 761	6
8	0899 400 762	6
9	0899 400 763	6
10	0899 400 764	6
11	0899 400 765	6

Related products	Art. No.
Glove holder with snap hooks	0899 899 023

Very comfortable and robust cut protection glove with Dyneema® fibres and breathable PU coating

- Excellent hand temperature and optimal comfort for long periods thanks to Dyneema® fibres
- Maximum comfort thanks to breathable PU coating
- High degree of abrasion resistance and mechanical resistance
- Good fit and flexibility

Application area

For applications with moderate cut protection and abrasion resistance requirements in dry work environments

CUT PROTECTION GLOVE W-210 LEVEL C



Gauge	15
Material of the liner	HDPE/glass fibre/polyester/elastane
Material coating	Nitrile foam
EN standard	388, 420
Cut resistance according to ISO 13997	C
Category	II

Size	Art. No.	P. Qty.
7	0899 403 607	6
8	0899 403 608	6
9	0899 403 609	6
10	0899 403 610	6
11	0899 403 611	6

Related products	Art. No.
Arm guard W-280 Level C	0899 400 420
Arm guard W-290 Level C	0899 400 421
Glove holder with snap hooks	0899 899 023

Universal, very comfortable cut protection glove with touch screen capability and additional reinforcement in the crook of the thumb

Ideal for operating screens with a capacitive touchscreen

Maximum comfort

Extremely breathable nitrile foam coating

Additional reinforcement in the crook of the thumb

Extended service life

Optimal fit and outstanding tactile and touch sensitivity

Suitable for precision work in dry conditions with high cut protection requirements

Application area

Work in dry work areas with cut protection stresses, e.g. storage and picking works, maintenance, metal and glass industry, recycling industry.