


## THREADED ROD

**DIN 976-1 (form A) with metric ISO standard thread, stainless steel A2**



|                              |                        |
|------------------------------|------------------------|
| <b>Standards</b>             | DIN 976-1              |
| <b>Material</b>              | Stainless steel A2     |
| <b>Form</b>                  | A                      |
| <b>Thread type</b>           | Metric thread          |
| <b>Identification colour</b> | Traffic green RAL 6024 |
| <b>RoHS-compliant</b>        | Yes                    |

| Thread type x nominal diameter (d <sub>1</sub> ) | Length (l <sub>1</sub> ) | Property class | Art. No.           | P. Qty. |
|--------------------------------------------------|--------------------------|----------------|--------------------|---------|
| M2                                               | 1000 mm                  | 70             | <b>0954 2</b>      | 10      |
| M3                                               | 1000 mm                  | 70             | <b>0954 3</b>      | 1/100   |
| M4                                               | 1000 mm                  | 70             | <b>0954 4</b>      | 1/100   |
| M4                                               | 3000 mm                  | 70             | <b>0954 003 4</b>  | 20      |
| M5                                               | 1000 mm                  | 70             | <b>0954 5</b>      | 1/100   |
| M5                                               | 2000 mm                  | 70             | <b>0954 002 5</b>  | 1/50    |
| M5                                               | 3000 mm                  | 70             | <b>0954 003 5</b>  | 1/25    |
| M6                                               | 1000 mm                  | 70             | <b>0954 6</b>      | 1/50    |
| M6                                               | 2000 mm                  | 70             | <b>0954 002 6</b>  | 1/25    |
| M6                                               | 3000 mm                  | 70             | <b>0954 003 6</b>  | 1/25    |
| M8                                               | 1000 mm                  | 70             | <b>0954 8</b>      | 1/50    |
| M8                                               | 2000 mm                  | 70             | <b>0954 002 8</b>  | 1       |
| M8                                               | 3000 mm                  | 70             | <b>0954 003 8</b>  | 1/10    |
| M10                                              | 1000 mm                  | 70             | <b>0954 10</b>     | 1/25    |
| M10                                              | 2000 mm                  | 70             | <b>0954 002 10</b> | 1       |
| M10                                              | 3000 mm                  | 70             | <b>0954 003 10</b> | 1       |
| M12                                              | 1000 mm                  | 70             | <b>0954 12</b>     | 1/25    |
| M12                                              | 2000 mm                  | 70             | <b>0954 002 12</b> | 1       |
| M12                                              | 3000 mm                  | 70             | <b>0954 003 12</b> | 1       |

### Notice

Stud bolts made from stainless austenitic steel with strength class A2-70 and nominal thread diameter  $d \geq 5$  mm, to be identified on one face as steel grade A2. As an alternative to the specified designation, stud bolts can be made identifiable on one end with the colour traffic green (RAL 6024).