



Brushable Body Sealing Compound

Sealing compound for recreating the original brush-stroke effect produced at the factory and for sealing of welds, seams, joints and overlaps in motor vehicles.

- Quick drying.
- Can be painted over.
- Silicone free.

Contents kg	Art. No.	Pack Qty.
1.2	0892 010	6

Characteristics

- Permanently elastic.
- Easily spreadable.
- Can be applied with a brush.
- Resistant to water and mineral oil.
- Good adhesive properties on untreated, primed and painted sheet metal.
- Unaffected by changes of temperature from -25°C up to $+80^{\circ}\text{C}$ (for short periods up to $+150^{\circ}\text{C}$).
- Base: Nitrile rubber.
- Colour: Light grey.
- Shelf life: 6 months at $+20^{\circ}\text{C}$; storage rooms should be well ventilated.

Application

Suitable for sealing of metal joints, cracks and overlaps, spot welds on front and rear sections, on boot floor, vehicle floor, passenger compartment, side panels and on wheel arches.



Nylon Brush

- Flat brush for the application of brushable sealing compound.
- Width 30 mm.

Art. No. 0693 30
Pack Qty. 1/10



Sealant

Soft, permanent-plastic, workable sealing material.

- For small repairs or work in places which are difficult to reach (sealing ruptured cables and lines for example).
- Can be moulded in your hand and then pressed into the seam etc. to be sealed.
- Colour: dark grey.
- Good adhesive properties.
- Shrink-resistant.
- Resistant to water.
- Temperature-resistant between -30°C and up to $+100^{\circ}\text{C}$, short-term (max. 5 min.) up to $+150^{\circ}\text{C}$.

Contents g	Art. No.	Pack Qty.
1000	0890 100 028	1/6