

Hammer drill H 26-MLS

Light and powerful hammer drill, equipped with exchangeable drill chuck and chisel function

Fast drilling progress and high removal performance when chiselling

High impact energy

For universal use

Drilling, rotary hammer drilling and chiselling with adjustable chisel position (3-mode function)

Comfortable

Lockable switch increases comfort for longer drilling/chiselling work.

Balanced power ratio in clockwise and anti-clockwise rotation

Rotating brush plate

Flexible applications

The quick-release chuck means that the tool can be converted from SDS drive arbour to a standard drill chuck in just a few steps.

Reduces risk of cable breakage

Ball grommet

2 Years WÜRTH MASTERPLUS Warranty for wear damage

The current WÜRTH MASTERPLUS warranty conditions must be observed.

3 Years Warranty on manufacturing and material defects

Excluded are damages caused by improper use, overloading or failure to observe the operating instructions.



Nominal voltage	230 V/AC
Frequency	50 Hz
Protection class	Protection class II/protective insulation
Power input	830 W
Min./max. idle speed	0-1300 rpm
Min./max. impact rate	0-4000 rpm
Tool holding device	Suitable for SDS-plus
Impact energy	2.7 J
Functions	Chisel function, Exchangeable chuck, Adjustable chisel position, Clockwise/anti-clockwise rotation, Impact stop for normal drilling, Throttle switch, Lock button for continuous operation
Min./max. drilling diameter in concrete	4-26 mm

Min./max. recommended drilling range for optimum performance (in concrete)	6-16 mm
Min./max. drilling diameter in steel	4-13 mm
Max. drilling diameter of hollow drill bit in masonry	68 mm
Weight of machine	2.9 kg
Cable length	4 m

Art. no. 5708 205 1

P. Qty.: 1

Details/Application

For concrete, masonry, steel and wood



Contents for art. no. 5708 205 1

Designation	Art. no.	Quantity
Plus Quadro-L Vario hammer drill bit 6 mm; Length 165 mm	0648 056 016	1
Plus Quadro-L Vario hammer drill bit Diameter:8 mm; Length:165 mm	0648 058 016	1
Plus Quadro-L Vario hammer drill bit Diameter:10 mm; Length:165 mm	0648 051 016	1
Quick-action drill chuck	0702 226 001	1
Maintenance spray	0893 051 702	1
Handle	5808 203 100	1
Case insert for MASTER machines	0955 031 203	1
System case 8.4.2	5581 011 000	1