

COMPRESSED AIR SAFETY COUPLING WSAFE® 2000 WITH COMFORT CONNECTION



Art. No.	0699 022 065	0699 022 080	0699 022 011
P. Qty.	3	3	3
Suitable for hose internal diameter	6.5 mm	8 mm	11 mm
Suitable for hose external diameter	10 mm	12 mm	16 mm
Length (L)	64 mm	68 mm	68 mm
Width across flats (SW)	20 mm	20 mm	24 mm

Related products	Art. No.
Soft Line cover caps for couplings Series 2000	0699 200 100

The compressed air coupling sets the benchmark in safety and efficiency when it comes to connecting PU pneumatic hoses.

Optimal compressed air supply and power delivery for compressed air consumers

Flow-optimised valve facilitates high flow rate of up to 2250 l/min and a maximum operating pressure of 16 bar. Result is greater productivity and lower energy costs for the user.

High protection and corrosion resistance even under demanding conditions

Exposed surfaces are chrome-plated, nickel-plated or galvanised.

Long service life

Locking sleeve made from hardened steel

Secure, one-handed decoupling

Safety coupling with single-stage decoupling process facilitates one-handed decoupling by pulling back locking sleeve. The coupling vents automatically with repelling of the hose prevented.

Euro profiles are compatible with other compressed air fittings

Series 2000 fittings comply with the European standard and have a nominal width of 7.6 mm.