

PAINT MARKER



Illustration only

Version	Permanently waterproof	
Shape of tip	Round tip	
Material of the housing	Aluminium	

Min./max. line thick- ness	Colour	Max. temperature resistance	Art. No.	P. Qty.
1-2 mm	Black	400 °C	0967 910 311	5
1-2 mm	Red	400 °C	0967 910 312	5
1-2 mm	White	1000 °C	0967 910 313	5
2-4 mm	Black	400 °C	0967 910 301	5
2-4 mm	Red	400 °C	0967 910 302	5
2-4 mm	White	1000 °C	0967 910 303	5

Heat-resistant up to 400°C

- Also for dark and transparent surfaces
- Waterproof and abrasion-resistant
- Light-resistant and weatherproof after drying
- Ink resistant to isopropyl alcohol, ethanol and engine oil

Application area

High-coverage markings, including on smooth and porous surfaces.

Ideal for use in metallurgy and forging,

mechanical engineering, metalworking and welding technology.









PASTE MARKER PAINTER



Illustration only



With twist mechanism to move forward the color paste

Line thickness	10 mm
Version	Permanently waterproof
Shape of tip	Round tip
Material of the housing	Plastic

	Colour	Art. No.	P. Qty.
	Black	0967 911 101	5
စ မ	Red	0967 911 102	5
	White	0967 911 103	5

Also ideal for surfaces with poor adhesion properties

- No sharpening
- With twist mechanism
- Can be used under water
- High-coverage, extra-permanent colour paste (also suitable for dark surfaces)
- Light-resistant and weatherproof after drying

Application area

Suitable for markings on concrete, masonry and wood. Suitable for use e.g. in agriculture and forestry, the construction industry, trade businesses and electrical/sanitary applications.