

Crimping Tools for cable lugs

For interchangeable half-shell
crimping inserts, width 22 mm

		
Model	Mechanical Hand Crimper WK 22	Hydraulic Crimping Tool WHK 60/22
Crimp. area mm ²	6.0 – 300.0	6.0 – 300.0
Press. force kN	–	60
Length approx. mm	stepless 560 – 830	400
Weight approx. g	3,500	2,800
Special features	- Crimping head rotates 360°, fold-open - Extended telescopic handles - With leverage	- Crimping head rotates 360°, fold-open - Two-stage hydraulics - Rapid feed - Automatic overpressure valve
Art. No.	0967 080 100	0967 080 120
P. Qty.	1	1
Accessories		
Steel sheet box		
Special features	Space for 13 crimping inserts	Space for 15 crimping inserts
Art. No.	0967 080 101	0967 080 121
P. Qty.	1	1

Half-Shell Crimping Inserts

Width 22 mm, for copper
conductors

Compatible to all Klauke crimping
tools for Series 22 crimping inserts
(K 22, HK 60/22, HK 60 UNV + UA22,
EK 22 PLUS, EK 60 UNV + UA22,
THK 22, PK 22, PK 60 UNV + UA22)

							
For	Pipe cable lugs common (similar to DIN) Art. No. 0967 2...  Art. No. 0967 3... 	Press-on cable lugs DIN 46235 Art. No. 0967 5...	Crimp ring terminals DIN 46234 Art. No. 0967 6...	Wire end ferrules Art. Pre-No. 0557 			
Die shape	Hexagon crimping 	Hexagon crimping 	Mandrel crimping 	Trapezoidal crimping 			
Cross-sec. in mm ²	Art. No.	P. Qty.	Art. No.	P. Qty.	Art. No.	P. Qty.	
10.0	0967 082 010	1	0967 085 010	1	0967 086 010	1	
16.0	0967 082 016	1	0967 085 016	1	0967 086 016	1	
25.0	0967 082 025	1	0967 085 025	1	0967 086 025	1	
35.0	0967 082 035	1	0967 085 035	1	0967 086 035	1	
50.0	0967 082 050	1	0967 085 050	1	0967 086 050	1	
70.0	0967 082 070	1	0967 085 070	1	0967 086 070	1	
95.0	0967 082 095	1	0967 085 095	1	0967 086 095	1	
120.0	0967 082 120	1	0967 085 120	1	0967 086 120	1	
150.0	0967 082 150	1	0967 085 150	1	—	0967 087 150	1
185.0	0967 082 185	1	0967 085 185	1	—	0967 087 185	1
240.0	0967 082 240	1	0967 085 240	1	—	—	