

## CABLE GLAND

PG

<b>Material</b>	<b>Polyamide PA6 V-2</b> , halogen and silicone-free
Sealing ring	Polychloroprene nitrile rubber CR/NBR, contains halogen
Temperature range	-20°C to +100°C
Protection type	IP68 - 5 bar
Color	Light gray, RAL 7035



	<b>Connecting thread</b>	<b>Cable dia. in mm (clamping range)</b>	<b>Thread length in mm</b>	<b>Wrench size in mm</b>	<b>Art. No.</b>	<b>P. Qty.</b>
	PG7	3-6.5	8	15	<b>0967 81 007</b>	100
	PG9	4-8		19	<b>0967 81 009</b>	
	PG11	5-10		22	<b>0967 81 011</b>	
	PG13.5	6-12	9	24	<b>0967 81 013</b>	
	PG16	10-14	10	27	<b>0967 81 016</b>	50
	PG21	13-18	11	33	<b>0967 81 021</b>	
	PG29	18-25		42	<b>0967 81 029</b>	25
	PG36	22-32	13	53	<b>0967 81 036</b>	10
	PG42	30-38		60	<b>0967 81 042</b>	5
	PG48	34-44		65	<b>0967 81 048</b>	

Storable in ORSY®

## LOCKNUT

PG

<b>Material</b>	<b>Polyamide PA6 GF30</b> , halogen and silicone-free
Temperature range	-20°C TO +100°C
Color	Light gray, RAL 7035

	<b>Connecting thread</b>	<b>Height in mm</b>	<b>Wrench size in mm</b>	<b>Art. No.</b>	<b>P. Qty.</b>
	PG7	5	19	<b>0967 85 007</b>	100
	PG9		22	<b>0967 85 009</b>	
	PG11		24	<b>0967 85 011</b>	
	PG13.5	6	27	<b>0967 85 013</b>	50
	PG16		30	<b>0967 85 016</b>	
	PG21	7	36	<b>0967 85 021</b>	5
	PG29		46	<b>0967 85 029</b>	
	PG36	8	60	<b>0967 85 036</b>	
	PG42		65	<b>0967 85 042</b>	
	PG48		70	<b>0967 85 048</b>	

Storable in ORSY®