

HEXAGON BOLTS

**With shaft in accordance with
DIN 931**

**With threading up to head
according to DIN 933**

Strength class 8.8U

**Hot-galvanized steel
(thermally galvanized = tzn)**

Thread dia. d	I in mm	DIN 933 full thread Art. No.	P. Qty.	DIN 931 with shaft Art. No.	P. Qty.
M12	20	0059 712 20	100/1		
	25	0059 712 25			
	30	0059 712 30			
	35	0059 712 35			
	40	0059 712 40			
	45	0059 712 45			
	50	0059 712 50			
	55	0059 712 55			
	60	0059 712 60			
	65	0059 712 65			
	70	0059 712 70		0059 612 70	
	80	0059 712 80		0059 612 80	
	90	0059 712 90		0059 612 90	
	100			0059 612 100	
	110			0059 612 110	
M16	120			0059 612 120	
	130			0059 612 130	
	140			0059 612 140	
	30	0059 716 30	50/1		
	35	0059 716 35			
	40	0059 716 40			
	45	0059 716 45			
	50	0059 716 50			
	55	0059 716 55			
	60	0059 716 60			
	65	0059 716 65			
	70	0059 716 70			
	75	0059 716 75			
	80	0059 716 80		0059 616 80	
	90	0059 716 90		0059 616 90	
	100	0059 716 100		0059 616 100	
M20	110	0059 716 110		0059 616 110	
	120	0059 716 120		0059 616 120	
	130			0059 616 130	
	140			0059 616 140	
	40	0059 720 40	25/1		
	45	0059 720 45			
	50	0059 720 50			
	55	0059 720 55			
	60	0059 720 60			
	65	0059 720 65			
	70	0059 720 70			
	75	0059 720 75			
	80	0059 720 80			
	90	0059 720 90			
	100	0059 720 100		0059 620 100	
	110	0059 720 110		0059 620 110	
	120	0059 720 120		0059 620 120	
	130			0059 620 130	
	140			0059 620 140	