

ELEVATOR TRIPOD



- Rugged aluminum construction.
→Low weight, yet highly stable.
- Quick-clamping lock.
- 5/8" screw thread.
- Attached catch strap.
→Prevents the tripod from slipping.
- With integrated elevator attachment and extension tube.
- Min. useful height: 80 cm.
- Max. useful height: 300 cm.
- Floor spikes with push-down pegs.
- With horizontal level.

Art. No. 0714 649 13

P. Qty. 1

Available in the fleet management system ORSY®fleet.

Extension Tube for elevator tripod

Art. No. 0714 649 130

P. Qty. 1

LASER TRIPOD



- Rugged aluminum construction.
- Quick-clamping lock.
- Length: 105 cm.
- Extendable to 160 cm.
- Floor spikes with push-down pegs.
- Flexible thanks to movable feet.

Art. No. 0714 64 421

P. Qty. 1

LASER GOGGLES



- Improves the detection of the laser point on all backgrounds.

Art. No. 0715 82 310

P. Qty. 1

TELESCOPIC LEVELING STAFF



- Min. length: 131 cm.
- Max. length: 242 cm.
- Aluminum construction.
- Millimeter increments.
- Measurement aid when leveling.

Art. No. 0714 64 425, P. Qty. 1