



ORSY

Cable Screw Connections

Brass

- Nickel-electroplated.
- Type of protection: IP 68 – 5 bar.
- With excellent strain relief and Neoprene seal.
- Temperature stability: -20°C to +100°C.
- Fully insulated.
- O-Ring at connecting thread.

Connecting thread	Cable clamp. range mm	Length of thread mm	Weight p. 100 pcs. kg	Art. No.	Pack Qty.
PG 7	3 - 6.5	5	1.17	0967 82 007	
PG 9	4 - 8	6	1.77	0967 82 009	100
PG 11	5 - 10	6	2.45	0967 82 011	
PG 13.5	6 - 12	6.5	2.82	0967 82 013	
PG 16	10 - 14	6.5	3.14	0967 82 016	
PG 21	13 - 18	7	5.40	0967 82 021	
PG 29	18 - 25	8	9.85	0967 82 029	25
PG 36	24 - 32	9	15.60	0967 82 036	10
PG 42	30 - 38	10	20.70	0967 82 042	
PG 48	34 - 44	10	29.70	0967 82 048	5



ORSY

Lock Nuts

Brass

- Nickel electroplated.
- According to DIN 46320.

Connecting thread	Wrench size mm	Thickness mm	Weight p. 100 pcs. kg	Art. No.	Pack Qty.
PG 7	15	2.8	0.20	0967 84 007	
PG 9	18	2.8	0.25	0967 84 009	
PG 11	21	3.0	0.30	0967 84 011	
PG 13.5	23	3.0	0.35	0967 84 013	
PG 16	26	3.0	0.50	0967 84 016	
PG 21	32	3.5	0.75	0967 84 021	
PG 29	41	4.0	1.25	0967 84 029	
PG 36	51	5.0	2.10	0967 84 036	
PG 42	60	5.0	3.15	0967 84 042	
PG 48	64	5.5	3.30	0967 84 048	50