

WRAPPING HOSE, STANDARD



- Spiral structure permits branches at any point
- Reusable

Application area

Bundling and cable protection of wires in cable fabrication, in the automotive and electrical industry and in switch and system construction.



Min./max. temperature resistance	-30 bis 80 °C
Flammability conditions	tested in accordance with UL94
Flammability	HB
Material	Polyethylene - PE
Halogen-free	Yes

Colour	Internal diameter	Min./max. bundle diameter (Bündel-Ø min./max.)	Wall thickness	Coil width	Art. No.	P. Qty.
Black	3.7 mm	4-20 mm	0.65 mm	7.0 mm	0771 00 40	25
Black	8.2 mm	12-50 mm	0.90 mm	12.0 mm	0771 00 80	25
Black	17.6 mm	20-120 mm	1.20 mm	22.0 mm	0771 00 90	25
Transparent	2.3 mm	2-15 mm	0.60 mm	5.0 mm	0771 00 16	50
Transparent	3.7 mm	4-20 mm	0.65 mm	7.0 mm	0771 00 42	25
Transparent	8.2 mm	12-50 mm	0.90 mm	12.0 mm	0771 00 82	25
Transparent	17.6 mm	20-120 mm	1.20 mm	22.0 mm	0771 00 92	25