

SET SCREWS

DIN EN ISO 4026

replaces DIN 913

with Allen socket and truncated cone

Bare steel, 45 H
Galvanized steel, blue passivated (A2K), 45 H

Hardness 45H corresponds to a hardness of 450 HV.

Nominal dia. d	Length l in mm	Bare steel Art. No.	P. Qty.	Galvanized steel Blue-passivated Art. No.	P. Qty.
M8	12	0255 8 12	100	0255 08 12	100
	14	0255 8 14		0255 08 14	
	16	0255 8 16		0255 08 16	
	18			0255 08 18	
	20	0255 8 20		0255 08 20	
	25	0255 8 25		0255 08 25	
	30	0255 8 30		0255 08 30	
	35	0255 8 35		0255 08 35	
	40	0255 8 40		0255 08 40	
	45	0255 8 45		0255 08 45	
	50	0255 8 50		0255 08 50	
	55	0255 8 55		0255 08 55	
	60	0255 8 60		0255 08 60	
	65	0255 8 65		0255 08 65	
	70	0255 8 70		0255 08 70	
	75	0255 8 75			
	80	0255 8 80		0255 08 80	
	85	0255 8 85			
	90	0255 8 90		0255 08 90	
M10	6	0255 10 6	100		100
	8	0255 10 8		0255 010 08	
	10	0255 10 10		0255 010 10	
	12	0255 10 12		0255 010 12	
	14	0255 10 14		0255 010 14	
	16	0255 10 16		0255 010 16	
	18	0255 10 18		0255 010 18	
	20	0255 10 20		0255 010 20	
	25	0255 10 25		0255 010 25	
	30	0255 10 30		0255 010 30	
	35	0255 10 35		0255 010 35	
	40	0255 10 40		0255 010 40	
	45	0255 10 45		0255 010 45	
	50	0255 10 50		0255 010 50	
	55	0255 10 55		0255 010 55	
	60	0255 10 60	50	0255 010 60	50
	65	0255 10 65		0255 010 65	
	70	0255 10 70		0255 010 70	
	75	0255 10 75			
	80	0255 10 80		0255 010 80	
	90	0255 10 90		0255 010 90	
	100	0255 10 100		0255 010 100	
	110	0255 10 110			
	120	0255 10 120		0255 010 120	
M12	8	0255 12 08	100		100
	10	0255 12 10		0255 012 10	
	12	0255 12 12		0255 012 12	
	14	0255 12 14		0255 012 14	
	16	0255 12 16		0255 012 16	
	18	0255 12 18			

DIN 913 has been retracted and replaced by international standard DIN EN ISO 4026.