

WAGO SCREWLESS CONNECTION TERMINAL



Illustration only

For all types of copper wire

Clamping range for fine-wire conductors

0.08–4.0 mm² (rated current 32 A)

Clamping range for single-wire and multi-wire conductors:

0.08–2.5 mm² (rated current 24 A)

Test opening for voltage testers

Application area

Suitable for all types of copper wire (single, multi and fine-wire). Lamps, blinds, awnings, door and gate controllers, intercom systems, pumps, vehicle electrical systems etc.

Min./max. wire cross section	0.08-4 mm ²
Nominal current	32 A
Min./max. wire-stripping length	9-10 mm
Nominal voltage	400 V
Max. ambient temperature	40 °C
Identification according to EN 60998	T85
Flammability	Self-extinguishing in accordance with UL94 V2
Material of the housing	Polyamide 6.6
Colour	Dark grey

Number of ladders	Art. No.	P. Qty.
2 PCS	0556 100 002	100
3 PCS	0556 100 003	50
5 PCS	0556 100 005	50

Compatible with ORSY storage system

Related products	Art. No.
Automatic self-adjusting wire stripping pliers	0714 109 010
Stripping knife AM 280	0714 41 01
Two-pin voltage tester Multi-Tester Pro II LCD	0715 53 175