

ATO FLAT PLUG-IN FUSE

Proof of performance

ISO 8820-3



Max. amperage	Color	Max. nominal voltage	Min./max. operating temperature	Surface of contacts	Art. No.	P.Qty.
1 A	Black	32 V/DC	-40 - 125 °C	Tin-plated	0731 001	25
1 A	Black	32 V/DC	-40 - 125 °C	Tin-plated		100
2 A	Gray	32 V/DC	-40 - 125 °C	Tin-plated	0731 002	25
2 A	Gray	32 V/DC	-40 - 125 °C	Tin-plated		100
3 A	Purple	32 V/DC	-40 - 125 °C	Tin-plated	0731 003	25
3 A	Purple	32 V/DC	-40 - 125 °C	Tin-plated		100
4 A	Pink	32 V/DC	-40 - 125 °C	Tin-plated	0731 004	25
4 A	Pink	32 V/DC	-40 - 125 °C	Tin-plated		100
5 A	Brown	32 V/DC	-40 - 125 °C	Tin-plated	0731 005	25
5 A	Brown	32 V/DC	-40 - 125 °C	Tin-plated		100
7.5 A	Ocher brown	32 V/DC	-40 - 125 °C	Tin-plated	0731 007 5	25
7.5 A	Ocher brown	32 V/DC	-40 - 125 °C	Tin-plated		100
10 A	Red	32 V/DC	-40 - 125 °C	Tin-plated	0731 010	25
10 A	Red	32 V/DC	-40 - 125 °C	Tin-plated		100
15 A	Turquoise	32 V/DC	-40 - 125 °C	Tin-plated	0731 015	25
15 A	Turquoise	32 V/DC	-40 - 125 °C	Tin-plated		100
20 A	Yellow	32 V/DC	-40 - 125 °C	Tin-plated	0731 020	25
20 A	Yellow	32 V/DC	-40 - 125 °C	Tin-plated		100
25 A	White	32 V/DC	-40 - 125 °C	Tin-plated	0731 025	25
25 A	White	32 V/DC	-40 - 125 °C	Tin-plated		100
30 A	Green	32 V/DC	-40 - 125 °C	Tin-plated	0731 030	25
30 A	Green	32 V/DC	-40 - 125 °C	Tin-plated		100
35 A	Blue	32 V/DC	-40 - 125 °C	Tin-plated	0731 035	25
35 A	Blue	32 V/DC	-40 - 125 °C	Tin-plated		100
40 A	Orange	32 V/DC	-40 - 125 °C	Tin-plated	0731 040	25
40 A	Orange	32 V/DC	-40 - 125 °C	Tin-plated		100

Suitable for ORSY storage