


### **ONE-EAR CLAMP WITH INSERT RING**





# Low overall height for connections in the tightest of spaces

## Low installation height, small clamping range

Precise assembly even in the narrowest spaces

Material	Stainless steel A2, 1.4307
Material of the insert ring	Stainless steel A2, 1.4307
Surface	Bare
RoHS-compliant	Yes

Width of band	Min./max. grip range	Diameter (Ø)	Art. No.	P. Qty.
5.5 mm	5.2-6.2 mm	6.6 mm	0541 066	100
6.4 mm	5.6-6.5 mm	7.0 mm	0541 070	100
6.4 mm	6.3-7.5 mm	8.0 mm	0541 080	100
7.4 mm	7.0-8.5 mm	9.0 mm	0541 090	100
7.4 mm	8.0-9.5 mm	10.0 mm	0541 100	100
7.4 mm	9.1-10.8 mm	11.3 mm	0541 113	100
7.4 mm	9.8-11.8 mm	12.3 mm	0541 123	100
8.2 mm	11.1-13.1 mm	13.8 mm	0541 138	100
8.2 mm	11.8-13.8 mm	14.5 mm	0541 145	100
8.2 mm	12.8-14.8 mm	15.5 mm	0541 155	100
8.2 mm	13.2-15.8 mm	16.5 mm	0541 165	100
8.2 mm	14.6-16.8 mm	17.5 mm	0541 175	100
8.2 mm	16.5-18.8 mm	19.5 mm	0541 195	100
9.2 mm	18.0-20.3 mm	21.0 mm	0541 210	100

Related products	Art. No.
Monier pliers	0715 02 04

#### **Application area**

Fuel line systems, air-conveying pipes, airbag, cooling water/heating, clamping/fastening, oil and lowpressure hydraulics

#### **Notice**

The outside diameter of the hose mounted on the connector should be approximately in the middle of the clamp's range.