



Fig.	Designation	Art. No.	P. Qty.
1	Complete Set, 20 m, 3 mm fiberglass profile	0975 800 020	
1	Complete Set, 30 m, 3 mm fiberglass profile	0975 800 030	
1	Complete Set, 50 m, 3 mm fiberglass profile	0975 800 050	
-	Replacement Strip, 20 m, 3 mm fiberglass profile	0975 801 020	1
-	Replacement Strip, 30 m, 3 mm fiberglass profile	0975 801 030	
-	Replacement Strip, 50 m, 3 mm fiberglass profile	0975 801 050	
-	Replacement Guide Head Set, 8 mm	0975 802 008	
-	Replacement Guide Head Set, 11 mm	0975 802 011	3
-	Replacement Guide Head Set, 14 mm	0975 802 014	
8	Replacement Guide Head Set with 8 mm, 11 mm and 14 mm heads	0975 802 100	1
4	Start Sleeve	0975 802 200	
5	Towing Ring	0975 802 300	3
6	Connection Sleeve	0975 802 400	
7	Klebfix Super Fast, 5 g	0893 090 0	1/25
3	Cable Towing Handle (rubber)	0975 802 500	
2	Cable Pulling Stocking, 4 - 6 mm	0975 803 004	
2	Cable Pulling Stocking, 6 - 9 mm	0975 803 006	
2	Cable Pulling Stocking, 9 - 12 mm	0975 803 009	
2	Cable Pulling Stocking, 12 - 15 mm	0975 803 012	1
2	Cable Pulling Stocking, 15 - 19 mm	0975 803 015	
2	Cable Pulling Stocking, 19 - 25 mm	0975 803 010	
2	Cable Pulling Stocking, 25 - 31 mm	0975 803 025	
-	Cable Lubricant in PVC container 500 g	0975 804 005	

Cable Installation System

Fiberglass, 3 mm dia.

- For easy cable installation with electrical, telephone and antenna cabling.
- Saves lots of time when installing cables.
- Stably-advancing, sliding sheathing on fiberglass profiles with a variety of guide heads.
- For use in partially-filled and heavily curved pipe systems and with very narrow bending radii.
- The high-quality fiberglass profile allows for extreme curves and bends with a minimum radius of 30 mm.
- Cable towing handle allows for maximum transmission of force.

Complete set comprised of:

- 3 mm fiberglass profile.
- Two start sleeves, attached on both sides.
- Three guide heads → 8, 11, 14 mm in diameter.
- Two connection sleeves (for repairs).
- Two towing rings.
- Two cable pulling stockings (4 - 6 mm and 6 - 9 mm).
- Fiberglass adhesive, 5 g, Art. No. 0893 090 0.
- Cable towing handle.
- Detailed operating instructions.
- Max. towing load: 100 kg.

Cable towing handle (Fig. 3)

