

PIPE CABLE LUG WITH INSPECTION HOLE

Common (similar to DIN)

Wire cross section	Flange hole	Wire diameter (d1)	Diameter of hole (d2)	Distance between sleeve end and centre of hole (e)	Sleeve length (a)	Width (b)	Art. No.	P. Qty.
70 mm ²	M8	12.0 mm	8.4 mm	43.0 mm	21.0 mm	23.0 mm	0967 270 8	25
70 mm ²	M10	12.0 mm	10.5 mm	45.0 mm	21.0 mm	23.0 mm	0967 270 10	25
70 mm ²	M12	12.0 mm	13.2 mm	46.0 mm	21.0 mm	23.0 mm	0967 270 12	25
70 mm ²	M16	12.0 mm	17.0 mm	49.0 mm	21.0 mm	28.0 mm	0967 270 16	25
95 mm ²	M8	13.5 mm	8.4 mm	48.0 mm	25.0 mm	26.0 mm	0967 295 8	25
95 mm ²	M10	13.5 mm	10.5 mm	48.0 mm	25.0 mm	26.0 mm	0967 295 10	25
95 mm ²	M12	13.5 mm	13.2 mm	49.0 mm	25.0 mm	26.0 mm	0967 295 12	25
95 mm ²	M16	13.5 mm	17.0 mm	52.0 mm	25.0 mm	28.0 mm	0967 295 16	25
95 mm ²	M20	13.5 mm	21.0 mm	58.0 mm	25.0 mm	36.0 mm	0967 295 20	25
120 mm ²	M8	15 mm	8.4 mm	51 mm	26 mm	28 mm	0967 212 08	25
120 mm ²	M10	15 mm	10.5 mm	51 mm	26 mm	28 mm	0967 212 010	25
120 mm ²	M12	15.0 mm	13.2 mm	51.0 mm	26.0 mm	28.0 mm	0967 212 012	25
120 mm ²	M16	15.0 mm	17.0 mm	53.0 mm	26.0 mm	30.0 mm	0967 212 016	25
150 mm ²	M10	16.5 mm	10.5 mm	58.0 mm	30.0 mm	31.0 mm	0967 215 010	25
150 mm ²	M12	16.5 mm	13.2 mm	58.0 mm	30.0 mm	31.0 mm	0967 215 012	25
150 mm ²	M16	16.5 mm	17.0 mm	58.0 mm	30.0 mm	31.0 mm	0967 215 016	25
150 mm ²	M20	16.5 mm	21.0 mm	64.0 mm	30.0 mm	36.0 mm	0967 215 020	25
185 mm ²	M10	19.4 mm	10.5 mm	65.0 mm	30.0 mm	36.0 mm	0967 218 510	25
185 mm ²	M12	19.4 mm	13.2 mm	65.0 mm	30.0 mm	36.0 mm	0967 218 512	25
185 mm ²	M16	19.4 mm	17.0 mm	65.0 mm	30.0 mm	36.0 mm	0967 218 516	25
185 mm ²	M20	19.4 mm	21.0 mm	69.0 mm	30.0 mm	39.0 mm	0967 218 520	25
240 mm ²	M10	21.2 mm	10.5 mm	72 mm	35 mm	39 mm	0967 224 010	25
240 mm ²	M12	21.2 mm	13.2 mm	72.0 mm	35.0 mm	39.0 mm	0967 224 012	25
240 mm ²	M16	21.2 mm	17.0 mm	72.0 mm	35.0 mm	39.0 mm	0967 224 016	25
240 mm ²	M20	21.2 mm	21.0 mm	72.0 mm	35.0 mm	39.0 mm	0967 224 020	25

Can be stored in ORSY system