

MEASURING ACCESSORIES

In accordance with the requirements of IEC/EN 61010-2-031

All products shown are equipped with a 4 mm safety plug with contact vanes or a jack designed for such a vane and are supplied in a reclosable blister pack for dust-proof storage.




Safety Test Leads with restrictable test tips

- Leads: Double-insulated, highly-flexible ultra-fine-wire silicone leads; 1 mm² cross-section
- Length: 1.2 m
- Measuring voltage/current: 1,000 V/CAT III, 20 A; 1,000 V/CAT II, 20 A
- 4 mm safety test tip with spring-action contact vane which is restrictable for use in various different measuring categories; opposite side features 4 mm dia. safety plug at 90° angle.
- Scope of delivery: One red measuring lead and one black measuring lead

Art. No. 0715 53 811

P. Qty. 1



Extensions for measuring leads

- With stackable 4 mm safety plugs on both sides
- Leads: Double-insulated, highly-flexible silicone stranded lead; 2.5 mm² cross-section
- Length: 1.5 m
- Measuring current/voltage: 1,000 V/CAT III, 32 A
- Scope of delivery: One red measuring lead and one black measuring lead

Art. No. 0715 53 820

P. Qty. 1




Safety Dolphin Clamps, fully insulated

- Clamping width: Max. 30 mm
- Measuring current/voltage: 1,000 V/CAT III, 32 A
- 4 mm safety jack in insulated body
- Scope of delivery: One red dolphin clamp and one black dolphin clamp

Art. No. 0715 53 830

P. Qty. 1



Safety Grippers, small, fully insulated

- Clamping width: Max. 11 mm
- Measuring current/voltage: Max. 300 V/CAT II, 15 A
- 4 mm safety jack in insulated body
- Delivery scope: One red gripper and one black gripper

Art. No. 0715 53 850

P. Qty. 1