

DRY DIAMOND CORE DRILL BIT FOR TILE M 14 MOUNT



••••



Specially developed diamond core drill bit for dry drilling of even the hardest materials like porcelain stoneware, for use with angle grinders.

Extremely fast drilling

Thanks to the vacuum diamond coating

Up to 14 mm dia. with special cooling wax

Easy core drill bit removal

Bits with dia. of less than 50 mm feature side slot

50 mm dia. and larger bits feature side slot and additional holes

Versatility	••○○
Service life	•••○
Drilling speed	••••
Drilled-hole quality	••○○
Spot-drilling behavior	••○○
Problem solver	•••○

Diameter	Length	Design	Art. No.	P.
5 mm	62 mm	Special cooling wax	5457 235 005	1
6 mm	62 mm	Special cooling wax	5457 235 006	1
8 mm	62 mm	Special cooling wax	5457 235 008	1
10 mm	62 mm	Special cooling wax	5457 235 010	1
12 mm	62 mm	Special cooling wax	5457 235 012	1
14 mm	62 mm	Special cooling wax	5457 235 014	1
15 mm	60 mm	Side slot	5457 235 015	1
16 mm	60 mm	Side slot	5457 235 016	1
18 mm	60 mm	Side slot	5457 235 018	1
20 mm	60 mm	Side slot	5457 235 020	1
22 mm	60 mm	Side slot	5457 235 022	1
25 mm	60 mm	Side slot	5457 235 025	1
27 mm	60 mm	Side slot	5457 235 027	1
28 mm	60 mm	Side slot	5457 235 028	1
30 mm	60 mm	Side slot	5457 235 030	1
32 mm	60 mm	Side slot	5457 235 032	1
35 mm	60 mm	Side slot	5457 235 035	1
38 mm	60 mm	Side slot	5457 235 038	1
40 mm	60 mm	Side slot	5457 235 040	1
42 mm	60 mm	Side slot	5457 235 042	1
44 mm	60 mm	Side slot	5457 235 044	1
45 mm	60 mm	Side slot	5457 235 045	1
50 mm	60 mm	Side slot and holes	5457 235 050	1
55 mm	60 mm	Side slot and holes	5457 235 055	1
60 mm	60 mm	Side slot and holes	5457 235 060	1
65 mm	60 mm	Side slot and holes	5457 235 065	1
68 mm	60 mm	Side slot and holes	5457 235 068	1
70 mm	60 mm	Side slot and holes	5457 235 070	1
75 mm	60 mm	Side slot and holes	5457 235 075	1
82 mm	60 mm	Side slot and holes	5457 235 082	1
90 mm	60 mm	Side slot and holes	5457 235 090	1
100 mm	60 mm	Side slot and holes	5457 235 100	1
110 mm	60 mm	Side slot and holes	5457 235 110	1
120 mm	60 mm	Side slot and holes	5457 235 120	1
128 mm	60 mm	Side slot and holes	5457 235 128	1

Application

- Especially suitable for tiles and porcelain stoneware with a material thickness up to 15 mm. Thicker materials up to the specified working length can be drilled, but more frequent cooling breaks are required.
- Suitable for hard ceramics, thin granite and marble plates and high-fired brick.